

# Approval and labeling



## for mobile working platforms (mobil scaffolds) according DIN EN 1004-1

Scaffolders \_\_\_\_\_ Qualified person at assembly \_\_\_\_\_  
Assembly period \_\_\_\_\_  
Qualified person for inspection \_\_\_\_\_  
Phone number \_\_\_\_\_ Inspection period \_\_\_\_\_  
Location \_\_\_\_\_ Client \_\_\_\_\_  
Scaffold-no. \_\_\_\_\_ Phone number \_\_\_\_\_

Load class/scaffolding group  2 (1,5 kN/m<sup>2</sup>)  3 (2,0 kN/m<sup>2</sup>)

The sum of the live loads of all superimposed scaffolding levels in a scaffolding field must not exceed the  
aforementioned value.

Access types  stairway (A)  stairladder (B)  inclined ladder (C)  vertical ladder (D)

Max. standing height (platform height) according to instruction manual / instruction for use

outdoors \_\_\_\_\_ m

indoors \_\_\_\_\_ m

Usage restrictions for the user

\_\_\_\_\_

\_\_\_\_\_



Do not make any unauthorized structural changes to the scaffolding! After adjusting and before stepping on the scaffolding, secure the swivel castors with spring clip. Carefully follow the instructions for assembly and use!

### Checked and approved

Qualified person for inspection of the manufacturer

Qualified person for inspection of the user

\_\_\_\_\_

\_\_\_\_\_

Date, Signature

Date, Signature