



Toe board for lateral exit railing

Length [mm]



2000



Specification

Length 2 m	Material Aluminium	Transport dimensions 1505 x 170 x 82 mm, 4.76 kg	Predecessor product 060989	Business division MUNK Günzburger Steigtechnik
Order no. 060962				

Facts

- Fall protection devices are required at exit points from vertical ladders and should preferably consist of railings on both sides of the vertical ladder, see DIN EN ISO 14122-4 and DIN 18799-3
- Required for roof parapet ≤ 150 mm
- Accessory package for art. 60960 consisting of: 1 x railing post, 1 x skirting board incl. mounting material



Scope of supply

Railing upright: 1 x

Board: 1 x

Installation material: 1 x

Assembly instructions: 1 x

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

RoHS

REACH

The MUNK Group complies with a Code of Conduct

The Supply Chain Act does not apply due to our size

The materials used are listed in the technical specification

Resource-saving production: own photovoltaic systems

Energy-efficient consumption during production: LED lighting

- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures





Added value

Optimum planning

- Practical planning aids (available as <u>Downloads</u>) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning





Corporate certifications

Standards for quality and sustainability









