



Order no.: 111007

# 3-section rope ladder with supports DIN EN 1147 photoluminescent

Rung covering

Glow (yellow luminescent)

Standard (red)

## Specification

| Rescue height<br>12.2 m                               | Intended use<br>Rescue                       | Ladder length retracted<br>5.6 m         | Ladder length extended<br>14 m                | Setting angle 70 °                   |
|---|--|--|---|--------------------------------------|
| Clear width between<br>rungs<br>270 mm                | Clear width, upper<br>ladder<br>350 mm       | Clear width, central<br>ladder<br>420 mm | Clear width, lower ladder<br>420 mm           | Outer width<br>500 mm                |
| Ladder feet<br>Steel point                            | Depth of side-rails<br>74                    | Step/Rung height<br>28 mm                | Step depth<br>29 mm                           | Number of steps/rungs<br>3x 17 rungs |
| Max. load capacity<br>324 kg                          | Persons max.                                 | Material<br>Aluminium                    | Rung covering<br>Glow (yellow<br>luminescent) | Weight<br>85 kg                      |
| Transport dimensions<br>6155 x 580 x 245<br>mm, 85 kg | Business division<br>MUNK<br>Rettungstechnik | Order no.<br>111007                      |   |                                      |

### **Facts**

- 3-section rope-extension ladder made of aluminium
- Rescue ladder compliant with DIN EN 1147



- With rope pulley, locking hook and rope brake
- Yellow luminescent, heat-insulating and non-slip plastic covering
- Supports made of aluminium tube with steel spikes and rubber jacketing
- 4-fold edged rung-to-side-rail connection
- Corrosion-resistant fixtures made of galvanised steel
- Lower ladder with steel spikes at the base
- Upper ladder with wall wheels
- Permissible load: 324 kg / 3 people

### Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard,
  small amounts of plastic
- No health hazards for the users

### More product pictures



# Corporate certifications

### on sustainability criteria









