



Order no.: 120110

Mobile container basic

Type

Base

Specification

Product type Base	Length 1.2 m	Width 800 mm	Height 1.19 m	Height up to top edge of extension 281 mm
Weight 36 kg	Transport dimensions 1200 x 800 x 1185 mm, 60 kg	Business division MUNK Rettungstechnik	Order no. 120110	

Facts

- **Modular and expandable:** The mobile container basic can be supplemented with additional add-on parts as required. Suitable for developing your own customised solutions by adding attachments and adaptations.
- **Stable and durable construction** made of high-strength aluminium sections
- **Ergo-Glow-Grip operation** via continuous handle bar with non-slip, cold-insulating SoftGrip coating
- **Robust and smooth-running actuating mechanism** via flexible Bowden cable
- **Two ball bearing castors** Ø 200 mm with central wheel slewing arrestor for optimum handling

- Two ball bearing fixed castors Ø 200 mm with drum brake and dead man's function, resistant to dust, moisture and oil
- Foot-operated parking brake
- Mobile container with "standard" undercarriage

Scope of supply

- Mobile container: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures

Added value

- The following equipment features are included as standard with every mobile container in the "Standard" assortment
- Body made of high-strength aluminium screw channel profile Connection of the profiles via stable, crossover corner screw connections – no welding!
- Markings for good visibility in the dark
- 2 fixed castors Ø 200 mm with internal drum brake and dead man's function
- 2 swivel castors Ø 200 mm with directional arrestors and central wheel and slewing arrestors
- Galvanised steel foot parking brake for swivel castors
- Operating control with ergonomic and continuous handle bars with SoftGrip coating
- Robust and smooth-running actuating mechanism via high-quality stainless steel Bowden cable

Corporate certifications

on sustainability criteria



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548



Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022

