

Order no.: 115350

Telescopic ladder red DIN EN 1147

Length [mm]

3500

4400



Specification

| | | | | |
|---------------------------|----------------------------------------|-----------------------------------|--------------------------------------------------------|----------------------------------------------|
| Rescue height 2.2 m | Intended use Rescue | Ladder length 3.5 m | Ladder length retracted 800 mm | Ladder length extended 3.5 m |
| Setting angle 70 ° | Clear width between rungs 270 mm | Outer width 500 mm | Depth of side-rails 100 mm | Width of side-rails 80 mm |
| Step/Rung height 28 mm | Step depth 29 mm | Number of steps/rungs 11 rungs | Max. load capacity 216 kg | Persons max. 2 |
| Material Aluminium | Rung covering Standard (red) | Weight 13.5 kg | Transport dimensions 940 x 560 x 130 mm, 13.5 kg | Business division MUNK Rettungstechnik |
| Order no. 115350 | | | | |

Facts

- Aluminium telescopic ladder
- Rescue ladder compliant with DIN EN 1147

- Abrasion-resistant anodised octagonal tube side-rails
- With heat-insulating, non-slip plastic coating (DE and THW (Federal Agency for Technical Relief) designs)
- Variable height adjustment via intuitive telescopic function (partial heights possible)
- Safety system for controlled retraction
- Minimises the risk of crushing and injury
- Permissible load: 250 kg / 2 people
- These products are covered by the statutory warranty

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures

Corporate certifications

on sustainability criteria



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548



Nachhaltigkeit

EcoVadis
sustainable supply management

CSR-Rating in Silber 2022

