MUNK
Sicherheit. Made in Germany.



Order no.: 120027

# Mobile container IBC

## Specification

| | | | | |
|---|---|---|---|---|
| Length<br>1.34 m | Width<br>800 mm | Height<br>1.34 m | Max. load capacity<br>700 kg | Castor diameter<br>200 mm |
| Braking system<br>Standard | Filling quantity of container<br>640 l | Number of levels<br>1 | Transport dimensions (plus packaging)<br>1350 x 800 x 1340 mm, 104 kg | Business division<br>MUNK Rettungstechnik |
| Order no.<br>120027 | | | | |

## Facts

- Mobile container in special dimension with "standard" undercarriage
- With IBC tank for holding liquids with a capacity of 640 l and a drain cock
- Connection adapters for Storz couplings are optionally available (part no. 120127)
- Including approval for hazardous goods
- Version with heavy-duty castors
- Further sizes and versions available on request



We reserve the right to make technical changes and price changes.

- Optionally also available with "Quadro" and
- "Quadro Light" undercarriage
- Scope of delivery without equipment items
- Series production quality equipment
- Stable and durable construction made of high-strength
- aluminium sections
- Platforms made of weatherproof wooden platform boards
- Ergo-Glow-Grip control unit – Continuous handlebar, oval-shaped for intuitive operation. Photoluminescent controls charge via UV radiation – for full functionality and safety even in the dark
- Robust and smooth-running actuating mechanism via flexible Bowden cable
- Two ball bearing castors Ø 200 mm with central wheel slewing arrestor for optimum handling
- Two ball bearing fixed castors Ø 200 mm with drum brake and dead man's function, resistant to dust, moisture and oil
- Foot-operated parking brake

## Scope of supply

- Mobile container: 1 x

## More product pictures







## Added value

- The following equipment features are included as standard with every mobile container in the "Standard" assortment
- Body made of high-strength aluminium screw channel profile Connection of the profiles via stable, crossover corner screw connections – no welding!
- Markings for good visibility in the dark
- 2 fixed castors Ø 200 mm with internal drum brake and dead man's function
- 2 swivel castors Ø 200 mm with directional arrestors and central wheel and slewing arrestors
- Galvanised steel foot parking brake for swivel castors
- Operating control with ergonomic and continuous handle bars with SoftGrip coating
- Robust and smooth-running actuating mechanism via high-quality stainless steel Bowden cable

MUNK
Sicherheit. Made in Germany.

# Corporate certifications

## Standards for quality and sustainability

Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022