MUNK
Sicherheit. Made in Germany.



Order no.: 120008

Mobile container portable fire pump suction hoses vertical

Suction hoses

upright | horizontal

Specification

Product type upright	Length 1.2 m	Width 800 mm	Height 1.19 m	Height up to top edge of platform 621 mm
Max. load capacity 500 kg	Castor diameter 200 mm	Braking system Standard	Business division MUNK Rettungstechnik	Order no. 120008

Facts

- Mobile container with "standard" undercarriage
- Folding operating unit for removing the suction hoses
- Suitable for holding the following equipment items:
- 1x portable fire pump PFPN 10-1500
- 4x suction hose A 1600 mounted vertically on the control unit
- 1x standpipe BB (DN80 / 2B)
- 1x underground hydrant wrench C
- 1x surface hydrant wrench B
- 3x coupling wrench ABC

We reserve the right to make technical changes and price changes.

- Drawer made of aluminium that can be pulled out on both sides (without brackets) for holding:
- 1x manifold A-BB
- 1x pressure hose B75 5 m
- 1x strainer basket A
- 1x wire protection cage A
- 2x multi-purpose line 20 m
- Fuel canister 10 l (low design)
- Further sizes and versions available on request
- Optionally also available with "Quadro" and "Quadro light" basic module
- Scope of delivery without equipment items
- Series production quality equipment
- Stable and durable construction made of high-strength aluminium sections
- Platforms made of weatherproof wooden platform boards
- Ergo-Glow-Grip control unit – Continuous handlebar, oval-shaped for intuitive operation. Photoluminescent controls charge via UV radiation – for full functionality and safety even in the dark
- Robust and smooth-running actuating mechanism via flexible Bowden cable
- Two ball bearing castors Ø 200 mm with central wheel slewing arrestor for optimum handling
- Two ball bearing fixed castors Ø 200 mm with drum brake and dead man's function, resistant to dust, moisture and oil
- Foot-operated parking brake

Scope of supply

- Mobile container: 1 x

More product pictures



Added value

- The following equipment features are included as standard with every mobile container in the "Standard" assortment
- Body made of high-strength aluminium screw channel profile Connection of the profiles via stable, crossover corner screw connections – no welding!
- Markings for good visibility in the dark
- 2 fixed castors Ø 200 mm with internal drum brake and dead man's function
- 2 swivel castors Ø 200 mm with directional arrestors and central wheel and slewing arrestors
- Galvanised steel foot parking brake for swivel castors
- Operating control with ergonomic and continuous handle bars with SoftGrip coating
- Robust and smooth-running actuating mechanism via high-quality stainless steel Bowden cable

MUNK
Sicherheit. Made in Germany.

Corporate certifications

Standards for quality and sustainability

Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022