

Order no.: 110006

Wooden hook ladder DIN EN 1147



Specification

Intended use Access	Ladder length 4.4 m	Ladder feet Steel point	Max. load capacity 150 kg	Persons max. 1
Material Wood	Weight 17 kg	Transport dimensions 4420 x 300 x 177 mm, 17 kg	Business division MUNK Rettungstechnik	Order no. 110006

Facts

- Wooden hook ladder
- Access ladder compliant with DIN EN 1147
- Side-rails made of finger-jointed pine or knot-free Oregon pine
- Rungs made of knot-free ash
- Folding hook made of galvanised steel secured with locking pin
- Spacer with rubber feet
- 10 climbing rungs firmly connected to the side-rails, 3 hook rungs and 1 deck rung

- Corrosion-resistant fixtures made of galvanised steel
- Permissible load: 108 kg / 1 person

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Corporate certifications

on sustainability criteria



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548

