MUNK
Sicherheit. Made in Germany.



Order no.: 040622

Single stepladder with nivello® traverse

Number of steps

12 | 14 | 16 | 18

Specification

Working height 4.3 m	Step design Steps	Number of steps/rungs 12 steps	Step width 371 mm	Step depth 80 mm
Step/Rung distance 235 mm	Type of non-slip protection Aluminium corrugated	Ladder length 3.14 m	Inclination 70 °	Base area 1.09 m
Outer width 420 mm	Stabiliser width 930 mm	Depth of side-rails 73 mm	Width of side-rails 25 mm	Max. load capacity 150 kg
Design type To lean against	Transport dimensions (plus packaging) 3105 x 425 x 116 mm, 9 kg	Business division MUNK Günzburger Steigtechnik	Order no. 040622	

Facts

- Aluminium step straight ladder
- Stable rectangular tube side-rails
- 80 mm deep, ribbed steps R10
- 4-fold edged step-to-side-rail connection
- ergo-pad® grip area
- Step spacing: 235 mm

- Ladder width: 420 mm (without stabiliser)
- Ladder inclination: 70°
- Maximum load: 150 kg
- nivello® stabiliser with optimum width for the selected product, ensuring an extra safe stance and ascent thanks to nivello® ladder shoes with 2-axis inclination technology, working angle check and exchangeable foot plates. The stabiliser is enclosed separately and is screwed to the lower end of the rail in two places

Scope of supply

- Ladder: 1 x
- Stabiliser (enclosed separately): 1 x

More product pictures



Added value

ergo-pad® grip area

For easier and more ergonomic handling at the optimum carrying point




roll-bar retrofit kit

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down



Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on TRBS 2121 Part 2 has been summarised on our Service page
- Read our tips and tricks on how to calculate working height



Certificates



25KFP0223-01 - Test Certificate "Bauart geprüft"

Valid in

DIN EN 131-1:2019
DIN EN 131-2:2017
DIN EN 131-3:2018
EK5/AK1 17-1.3:2021
PAK-ANFORDERUNG FÜR GS (PAH REQUIREMENT FOR GS) AFPS GS 2019:01 PAK

MUNK
Sicherheit. Made in Germany.

Corporate certifications

Standards for quality and sustainability

Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022