MUNK
Sicherheit. Made in Germany.



Order no.: 036628

# 2-section GRP rung extension ladder with nivello® traverse

Number of rungs

2x8 | 2x10 | 2x12

## Specification

| | | | | |
|---|---|---|---|---|
| Working height<br>5.2 m | Step design<br>Rungs | Number of steps/rungs<br>2x 8 rungs | Step/Rung height<br>29 mm | Step depth<br>28 mm |
| Step/Rung distance<br>280 mm | Retracted length<br>2.5 m | Extended length<br>4.18 m | Outer width<br>420 mm | Stabiliser width<br>930 mm |
| Depth of side-rails<br>73 mm | Width of side-rails<br>25 mm | Design type<br>To lean against \| 2-part | Transport dimensions (plus packaging)<br>2440 x 430 x 144 mm, 16.9 kg | Predecessor product<br>036608 |
| Business division<br>MUNK Günzburger Steigtechnik | Order no.<br>036628 | | | |

## Facts

- Rung push-up extension ladder made of glass-fibre reinforced plastic
- Side-rails and rungs made of reinforced fibre glass plastic profiles
- Rectangular rungs grooved on both sides, 28 x 29 mm

- By using the metal suspension step, the insulation voltage is reduced to 1,000 V
- High-strength rung-to-side-rail connection
- Galvanised steel fittings
- Easy height adjustment from rung to rung
- Upper ladder from size 2 x 12 with wall wheels
- Corrosion-resistant guide fixtures
- Upper ladders up to 3.0 m with nivello® ladder shoes
- Rung distance: 280 mm
- Ladder width: 420 mm (without stabiliser)
- Maximum load: 150 kg
- Standard stabiliser with non-slip ladder shoes with optimum width for the selected product. Ensures maximum stability and safe ascent for straight ladders over 3.0 m. The stabiliser is enclosed separately and is screwed to the lower end of the rail in two places
- Suitable for working near or on live parts
- Tested in accordance with DIN EN 61478:2002 + DIN EN 61478/A1:2004, Section 6.5.1, Category 1: 24,500 V
- Note: In accordance with standards, the attached push-up extension ladder section cannot be separated from the ladder with lengths over 3.0 m
- Please note: Due to their delicate nature, products containing GRP cannot be returned.

## Scope of supply

- Ladder: 1 x
- Stabiliser (enclosed separately): 1 x

## More product pictures





## Added value

Optimum and smooth operation, thanks to easily accessible elements

- Simple height adjustment from rung to rung or from step to step
- Wall wheels on the upper part (from 14 rungs or more)
- Fittings with sliding guides
- Smooth-running rope pulley



Fiberglass

Ladders made of GFRP offer the perfect properties for special challenges. Find out what makes GFRP such a special material, how we use it for ladders and where these ladders are used.



Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



MUNK
Sicherheit. Made in Germany.

# Corporate certifications

## Standards for quality and sustainability

Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022