


Order no.: 070982

# Rigid climbing aid







2

3

4





## **Specification**

Platform height <b>200 mm</b>	Top surface depth 295 mm	Top surface width <b>550 mm</b>	Step/Platform surface Aluminium tibial plate	Non-slip class R10
Base area length 370 mm	Base area width 590 mm	Design type Single-sided access   Rigid	Number of steps/rungs 1 steps	Platform included as step <b>Yes</b>
Max. load capacity 150 kg	Material <b>Aluminium</b>	Transport dimensions 580 x 335 x 205 mm, 3 kg	Business division MUNK Günzburger Steigtechnik	

#### **Facts**

- Aluminium climbing aid
- Sturdy, welded bar design
- 220 mm deep steps made of aluminium chequered plate for a secure footing
- Top tread surface: 550 x 300 mm
- Non-slip plastic shoes
- Step spacing 200 mm
- Maximum load: 150 kg

### **Description**

The rigid climbing aid offers the perfect combination of stability and comfort. Designed for riders and stable owners, it is the ideal support for safe mounting while saddling, grooming or riding. The non-slip aluminium chequered plates (R10) ensure stability and protect against slipping – even in damp conditions.

### Advantages at a glance



- Maximum safety: Robust aluminium construction with non-slip plastic feet for a firm hold on any surface.
- **Ergonomic design:** Comfortable step spacings and generous tread areas provide comfort and support gentle mounting, which relieves the horse's back.
- **Flexibility:** Various models with up to 5 steps offer the right solution for every situation, from everyday care to use in the riding arena.

#### Your added value

With the rigid climbing aid, you invest in safety and longevity. The space-saving design and sustainable production guarantee added value for your everyday stable life and your horse's health

### Scope of supply

Platform: 1 x

Instructions for use and operation: 1 x

## Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany



- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

### More product pictures









#### Added value

#### Safe working

- Handrails for safe ascent and descent
- Large-format, non-slip platforms
- Sturdy designs for secure stance



#### From small to large

- The right product for every application
- One-sided and two-sided variants



#### **Industrial grade**

- Robust design for demanding applications
- Use of high-quality and high-strength materials



#### Non-slip plastic shoes

- Ensure secure stance
- High impact and abrasion resistance
- Simple replacement in the event of wear





# **Corporate certifications**

on sustainability criteria









