



Order no.: 033319

3-section multi-purpose ladder with steps with nivello® stabiliser and clip-step R13



Number of steps

3x6

3x7

3x8

Specification

Working height 5.2 m	Step design Steps	Number of steps/rungs 3x 6 steps	Step depth 80 mm	Step/Rung distance 263 mm
Ladder length, three-part, straight 4.18 m	Ladder length, 2-part, double-sided with attachable section 3.06 m	Base spread as double ladder 1.32 m	Inclination 70 °	Retracted length 1.96 m
Outer width 490 mm	Stabiliser width 930 mm	Depth of side-rails 85 mm	Width of side-rails 25 mm	Max. load capacity 150 kg
Weight 22.46 kg	Transport dimensions 1930 x 500 x 290 mm, 22.462 kg	Business division MUNK Günzburger Steigtechnik	Order no. 033319	Price € 1,241.00

Facts

- Multi-purpose ladder with steps made of aluminium
- Stable rectangular tube side-rails
- Grooved steps with a depth of 80 mm
- 4-fold edged step-to-side-rail connection

- nivello® ladder shoes and nivello® stabiliser (enclosed separately)
- Can be used as a step ladder, straight ladder and push-up extension ladder
- Simple height adjustment and secure locking thanks to insertion hook with automatically engaging lift-off protection
- Upper ladder with wall wheels
- Spreader lock with two high-strength polyester straps and detachable metal strut
- Step spacing: 263 mm
- Ladder width: 490 mm (without stabiliser)
- Ladder inclination: 70°
- Maximum load: 150 kg
- clip-step R13 step padding for certified non-slip protection
- Lowest step on each ladder section with clip-step R13 finished in yellow

Scope of supply

- Ladder: 1 x
- Stabiliser (enclosed separately): 1 x
- Instructions for use and operation: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification

- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures

Added value

roll-bar retrofit kit

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down



Flexibility

- Universal and versatile use
- Compact size for transport and storage
- Upper ladder can also be used individually (up to 3.0 m)



The movable ladder shoe sets new standards in stability

[Learn more](#)



Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



nivello® stabiliser


Extra safe, standards-compliant ascent for straight ladders over 3.0 m

- Extra wide stabiliser for even greater stability
- nivello® ladder shoes with patented 2-axis inclination technology, integrated work angle check and exchangeable foot plates
- Individually available as spare part



Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)



Easy handling

- Insertion hooks with lift-off protection or automatically locking steel hinges
- Optimised guidance, thanks to guide fixtures with high-strength plastic coating

Corporate certifications

on sustainability criteria



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548

