MUNK
Sicherheit. Made in Germany.



Order no.: 031320

Multi-function ladder, 4-section, with nivello® stabiliser and wooden surface.

Number of rungs

2x2 + 2x3 | 2x3 + 2x4 | 4x3

Specification

Working height 4 m	Step design Rungs	Number of steps/rungs 2x2 Sp. 2x3 Sp.	Step/Rung height 30 mm	Step depth 30 mm
Step/Rung distance 280 mm	Ladder length as straight ladder 2.85 m	Ladder length as double-sided ladder 1.49 m	Base spread as double ladder 990 mm	Inclination 70 °
Height as working platform 630 mm	Length as working platform 1.4 m	Base spread as working platform 2.17 m	Outer width 350 mm	Stabiliser width 930 mm
Depth of side-rails 58 mm	Width of side-rails 25 mm	Max. load capacity 150 kg	Transport dimensions (plus packaging) 933 x 360 x 273 mm, 12.5 kg	Transport dimensions (plus packaging) 2 1425 x 290 x 32 mm, 4 kg
Business division MUNK Günzburger Steigtechnik	Order no. 031320			

Facts

- Aluminium multi-function rung ladder
- Stable rectangular tube side-rails

- Rectangular rungs grooved on both sides, 30 x 30 mm, Slip resistance class R10
- 4-fold edged rung-to-side-rail connection
- Can be used as step and straight ladder and as work platform (required accessories included)
- Optimum operational safety due to six automatically locking steel hinges
- nivello® stabilisers for extra safe stance and ascent (double-sided, enclosed separately)
- Rung distance: 280 mm
- Ladder width: 350 mm
- Maximum load: 150 kg

Scope of supply

- Ladder: 1 x
- Stabiliser (enclosed separately): 2 x
- Wood flooring for use as a work floorboard: 1 x
- Instructions for use and operation: 1 x

More product pictures











Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Easy handling

- Insertion hooks with lift-off protection or automatically locking steel hinges
- Optimised guidance, thanks to guide fixtures with high-strength plastic coating

Flexibility

- Universal and versatile use
- Compact size for transport and storage
- Upper ladder can also be used individually (up to 3.0 m)



Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



The movable ladder shoe sets new standards in stability

Learn more



nivello® stabiliser

Extra safe, standards-compliant ascent for straight ladders over 3.0 m

- Extra wide stabiliser for even greater stability
- nivello® ladder shoes with patented 2-axis inclination technology, integrated work angle check and exchangeable foot plates
- Individually available as spare part



roll-bar retrofit kit

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down



Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on TRBS 2121 Part 2 has been summarised on our Service page
- Read our tips and tricks on how to calculate working height



MUNK
Sicherheit. Made in Germany.

Corporate certifications

Standards for quality and sustainability

Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022