MUNK
Sicherheit. Made in Germany.



Order no.: 681200

# Stationary de-icing system, complete

platform length

15960

## Specification

| | | | | |
|---|---|---|---|---|
| Platform length<br>15.96 m | Platform width<br>850 mm | Platform height<br>3 m | Height<br>4.1 m | Total width<br>960 mm |
| Railing height<br>1.1 m | Transport dimensions (plus packaging)<br>5000 x 1100 x 1500 mm, 250 kg | Transport dimensions (plus packaging) 2<br>3200 x 1350 x 1400 mm, 500 kg | Business division<br>MUNK Günzburger Steigtechnik | Order no.<br>681200 |

## Facts

- For the safe and quick removal of ice and snow loads from trucks and commercial vehicles. Also ideal for repairs to truck tarpaulins and superstructures.
- Maintenance-free design made of corrosion-resistant aluminium profiles and stainless steel connecting parts for stationary installation
- Individual total lengths and configurations possible thanks to efficient modular design
- Step and platform surfaces made of non-slip steel grating (R12) for all weather conditions. The hole pattern also prevents the accumulation of dirt, snow and water



We reserve the right to make technical changes and price changes.

- Convenient access to the walkway via 45° stairway with handrails on both sides and automatically closing safety door
- Railings on both sides with foot and knee boards ensure a high level of safety at work (height: 1,100 mm)
- Easy installation thanks to delivery in pre-assembled modules including assembly instructions
- The design takes account of DIN EN ISO 14122-2 and -3
- Maximum load: 1.5 kN/m2, step load 150 kg, total load 300 kg
- Production in compliance with European standards DIN EN ISO 14122 and DIN EN 1004
- This product is made to order and cannot be returned

## Scope of supply

- Installation material: 1 x
- Assembly instructions: 1 x

## More product pictures











## Added value

### Product configurator

Configuring, enquiring about and ordering individual products could not be easier with our product configurator for stairs, bridging steps and mobile platform stairs. Simply enter your required dimensions and versions step by step, and a rotating 3D model will appear in real time. To save your configuration and request a quotation requires a login which will be set up for you by our Sales team.



### Modular kit system

- Individually and cost-efficiently combinable for the respective requirement
- Platform heights from 1.25 to 3.0 m
- Three different platform lengths can be selected

### Safety railing

- Railings and handrails on both sides ensure a high level of safety at work
- Fixed size or telescopic safety door



### Ascent

- Non-slip designs for secure footing
- All kinds of different materials can be selected with non-slip classes from R 9 to R 13 – suitable for the specific application purpose



Modular walkway systems

- For a wide range of indoor applications in production, warehouses, as access to machines, as a walkway along building walls or as practical access for de-icing commercial vehicles in the winter months
- Thanks to innovative modular construction, walkway systems can be assembled conveniently, cost-effectively and yet precisely to meet individual requirements
- The platform height of the walkway systems can be individually determined between 1.25 and 3.0 metres. The desired total length is achieved by way of combining three different walkway lengths
- The modules can be easily assembled using pre-assembled modules, securely connected to one another and fastened to the underlying surface using foot brackets
- The maintenance-free modules are manufactured as a stable, corrosion-resistant aluminium construction with a supporting frame.
- Maximum load: 1.5 kN / m², step load 150 kg, total load 300 kg
- Access to the walkway conveniently via stairs 45° with handrails on both sides and automatically closing safety door.
- The delivery from the factory is made in pre-assembled modules for quick and simple assembly in accordance with the enclosed assembly instructions

Note

When assembling a walkway, only modules with the same platform height can be combined. Please contact us if you need different platform heights on a walkway system. This also applies if you need walkway systems for outdoor use, as they are primarily designed for indoor use (with the exception of de-icing systems).

# Corporate certifications

## Standards for quality and sustainability

