MUNK
Sicherheit. Made in Germany.



Order no.: 052088

Push-fit section for push-fit platform ladder

Number of additional steps

1 2 3 4 5

Specification

Working height 2.91 m	Step design Steps	Number of steps/rungs 1 steps	Platform included as step No	Platform height 910 mm
Non-slip class R10	Step depth 80 mm	Step/Rung distance 235 mm	Height 1.66 m	Base spread 990 mm
Inclination 70 °	Lower outer width 570 mm	Depth of side-rails 73 mm	Depth of side-rails, support 58 mm	Max. load capacity 150 kg
Design type Freestanding | Single-sided access	Transport dimensions (plus packaging) 453 x 533 x 178 mm, 4.58 kg	Business division MUNK Günzburger Steigtechnik	Order no. 052088	

Facts

- Four different push-fit sections for flexible extension of the platform ladder range
- Easy and fast installation, thanks to push-fit connectors with hook lock
- Coloured coating of the beams for easy pairing identification
- Space-saving transport and storage

Description

This product only includes the push-fit section for the push-fit platform ladder. The main platform ladder is available as a version with two handrails or with a foldable handle.

We reserve the right to make technical changes and price changes.

- Note: Height data and base spread measured in conjunction with the platform ladder (push-fit) (order no. 052083)

Scope of supply

- Push-fit section: ascending part: 1 x
- Push-fit section: support part: 1 x

More product pictures











Added value

Safe working

- Handrails for safe ascent and descent
- Large-format, non-slip platforms
- Conical side-rail guide for safe stance
- Railings and knee boards for safe access and stance



Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Ladder joint safe-cap

- Smooth ladder joint with large contact surface and sturdy plastic protective cap
- The 6 rivets and thicker wall thickness provide for greater stability and protection at this sensitive point on the ladder, increasing its service life
- The safe-cap protects the ladder when in use, when loading and storing, as well as the contact surfaces, walls, truck loading areas and the joint itself



clip-step step padding

Optimised and certified non-slip protection for greater comfort and safety

- Made of grooved plastic
- Exact fit and easy to clip onto the steps
- Applied up to the maximum accessible step as a visual check
- Retrofittable and available as spare part



clip-step R 13 step padding

Certified non-slip protection for step ladders

- Fulfils the requirements of the highest possible non-slip class R 13 thanks to aluminium oxide particles
- Improves work safety in wet and oil-contaminated environments
- Applied up to the maximum accessible step as a visual check
- Retrofittable, available as a spare part and also in yellow in selected lengths (RAL 1021)



Castors

- Ergonomic and comfortable handling
- Simple movement from place to place



Sponsored by BG BAU

Specification subject to conditions; for the latest information please visit the BG BAU website (statutory accident insurance company for the construction and construction related services in Germany). Since 2014, the BG BAU has been promoting the purchase of platform ladders, step stools and ladder accessories with single-sided and double-sided access. All members of the BG BAU profit from this. This aims to prevent work accidents on building sites and improve ergonomic working practices. For more information by BG BAU, please visit:
www.bgbau.de/service/angebote/arbeitsschutzpraemien

A brief overview of the subsidy and an overview of our eligible products can be found on our website under know-how.

Corporate certifications

Standards for quality and sustainability

