MUNK
Sicherheit. Made in Germany.



Order no.: 127129

FlexxLift 5.0 MD

Specification

Working height 2.15 - 5 m	Platform height 0.15 - 3 m	Platform length 0.89 m	Platform width 645 mm	Base area length 1.23 m
Base area width 770 mm	Approved for outdoor use No	Max. load capacity 180 kg	Transport dimensions (plus packaging) 1230 x 770 x 1765 mm, 380 kg	Business division MUNK Günzburger Steigtechnik
Order no. 127129				

Facts

- Vertical mast lift with a working height of 5.00 m
- Battery-powered drive and lifting system, self-propelled and emission-free
- Operated via joystick
- Fits through standard doorways and is suitable for lifts thanks to its compact transport dimensions
- Suitable for delicate floors thanks to its low weight

Description

If you’re constantly changing position, you waste time moving the platform around. The FlexxLift 5.0 MD self-propelled vertical mast platform lifts and moves you to a working height of 5.00 m via a joystick – smoothly and quietly. You control it, rather than pushing it.

Self-propulsion and lifting via joystick

Both travel and lifting are battery-powered and emission-free – you operate both via the joystick.

We reserve the right to make technical changes and price changes.

- 24V battery technology with integrated charger (Schuko plug, 230 V)
- Battery level indicator
- Travelling speed up to 4 km/h, reduced depending on working height
- Open work basket with horizontal knee rail
- Handy storage for tools etc.
- Max. load capacity 180 kg (1 person + equipment)
- Forklift pockets and lifting eyes
- Tested in accordance with DIN EN 280-1 (Class 3A)

Instead of pushing the platform to the next location, you drive there and raise yourself to the required height. At speeds of up to 4 km/h, reduced depending on height for safety.

Battery charge level and operating hours at a glance

You can charge the maintenance-free 24 V system via the integrated charger – no external device is required. The operating hours counter and battery charge level indicator show you exactly where you stand at all times. If the battery runs flat, the emergency lowering function and decouplable drive system keep the platform mobile, so you can still move it out of the way.

Open basket – loaded from the side, without having to reach over

In the open basket, you can load and unload your materials conveniently from the side, rather than having to lift them over a high edge. This means you can reach items in the lower section effortlessly too.

Low kerb weight

Weighing just 380 kg, the platform remains light enough to protect sensitive floors.

Tested safety – with certification

The platform is tested in accordance with DIN EN 280-1 (Class 3A); the CE Declaration of Conformity and test report are available in German. A 12-month warranty applies.

Request your quote now.

Scope of supply

- Lift: 1 x
- Instructions for use and operation: 1 x

More product pictures







MUNK
Sicherheit. Made in Germany.

Corporate certifications

Standards for quality and sustainability

Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022