MUNK
Sicherheit. Made in Germany.



Order no.: 116125

# Equipment maintenance ladder

## Specification

| | | | | |
|---|---|---|---|---|
| Working height<br>4.7 m | Number of steps/rungs<br>2x 6 rungs | Step width<br>300 mm | Step/Rung height<br>30 mm | Step depth<br>30 mm |
| Step/Rung distance<br>280 mm | Type of non-slip protection<br>Aluminium corrugated | Length of ladder sections<br>1.7 m | Ladder length as straight ladder<br>3.6 m | Ladder length as double-sided ladder<br>1.85 m |
| Base spread as double ladder<br>1.21 m | Inclination<br>72.5 ° | Stabiliser width<br>649 mm | Depth of side-rails<br>58 mm | Width of side-rails<br>25 mm |
| Max. load capacity<br>150 kg | Design type<br>Freestanding \| Double-sided access | Business division<br>MUNK Rettungstechnik | Order no.<br>116125 | |

## Facts

- Aluminium folding rung ladder
- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm, Slip resistance class R10
- 4-fold edged rung-to-side-rail connection
- Can be used as a step and straight ladder



We reserve the right to make technical changes and price changes.


- nivello® ladder shoes with patented 2-axis inclination technology
- Optimal operational safety thanks to two automatically locking steel hinges
- Stabiliser for extra safe footing and ascent (enclosed separately)
- Rung distance: 280 mm
- Ladder width: 350 mm
- Maximum load: 150 kg
- Side-rail and stabiliser powder-coated in red
- Foil lettering on one side "Die Gerätewartleiter"

## Scope of supply

- Ladder: 1 x
- Instructions for use and operation: 1 x

## More product pictures




MUNK
Sicherheit. Made in Germany.

# Corporate certifications

## Standards for quality and sustainability

Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022