

Order no.: 116125

## Equipment maintenance ladder



### Specification

Working height 4.7 m	Number of steps/rungs 2x 6 rungs	Step width 300 mm	Step/Rung height 30 mm	Step depth 30 mm
Step/Rung distance 280 mm	Type of non-slip protection Aluminium corrugated	Length of ladder sections 1.7 m	Ladder length as straight ladder 3.6 m	Ladder length as double-sided ladder 1.85 m
Base spread as double ladder 1.21 m	Inclination 72.5 °	Stabiliser width 646 mm	Depth of side-rails 58 mm	Width of side-rails 25 mm
Max. load capacity 150 kg	Design type Freestanding   Double-sided access	Weight 9 kg	Transport dimensions x x mm, 9 kg	Business division MUNK Rettungstechnik
Order no. 116125				

### Facts

- Aluminium folding rung ladder
- Stable rectangular tube side-rails

- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection
- Can be used as a step and straight ladder
- Optimum operational safety due to six automatically locking steel hinges
- nivello® ladder shoes with patented 2-axis inclination technology
- Stabiliser for extra safe footing and ascent (enclosed separately)
- Rung distance: 280 mm
- Ladder width: 350 mm
- Maximum load: 150 kg
- Side-rail and stabiliser powder-coated in red
- Foil lettering on one side "Die Gerätewartleiter"

### Scope of supply

- Ladder: 1 x
- Instructions for use and operation: 1 x

### Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany

- **Recyclability:** Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- **Socially acceptable working conditions in production:** fair wages, gender equality
- **Economical and recyclable packaging:** no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- **No health hazards for the users**

More product pictures

---

## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

