MUNK
Sicherheit. Made in Germany.



Order no.: 033806

Double-sided stepladder wood

Number of steps/rungs

2x3 | 2x4 | 2x5 | 2x6 | 2x7 | 2x8

Specification

Working height 2.25 m	Step design Steps + Rungs mixed	Number of steps/rungs 2x 3 steps	Step/Rung height 20 mm	Step depth 80 mm
Step/Rung distance 250 mm	Ladder length 970 mm	Total length folded 970 mm	Base spread 750 mm	Inclination 70 °
Lower outer width 440 mm	Upper outer width 340 mm	Depth of side-rails 65 mm	Width of side-rails 22 mm	Max. load capacity 150 kg
Design type Freestanding | Double-sided access	Transport dimensions (plus packaging) 970 x 440 x 160 mm, 5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 033806	

Facts

- Double-sided stepladder made of wood
- Solid softwood timber side-rails, beech steps
- Grooved steps with a depth of 80 mm R10
- Die obersten beiden Sprossen aus Buche 22 x 44 mm

We reserve the right to make technical changes and price changes.

- Pegged step-to-side-rail connection, resulting in smooth side-rail surface
- Sturdy steel hinges
- Supplied as standard with practical bucket hook
- Spread protection through firmly screwed textile straps
- plastic transport lock at the base of the ladder
- Step spacing: 230 mm
- Ladder inclination: 70°
- Maximum load: 150 kg

Scope of supply

- Ladder: 1 x

More product pictures







Added value

Industrial grade

- Sturdy processing for demanding applications (e.g. 4-fold edging)
- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories

Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on TRBS 2121 Part 2 has been summarised on our Service page
- Read our tips and tricks on how to calculate working height



MUNK
Sicherheit. Made in Germany.

Corporate certifications

Standards for quality and sustainability

