



Order no.: 154349

# Mobile scaffolding SG 0.75 × 1.8 m with outrigger

Platform height [mm]

3070	4470	5590	6430	7550	8390	9510
10350						

# Specification

Working height 5.07 m	Scaffolding height 4.34 m	Platform height 3.07 m	Platform width 750 mm	Platform length 1.8 m
Load capacity 2 kN/m2	Weight 123 kg	Transport dimensions 3100 x 800 x 650 mm, 122 kg	Indoor use, central installation possible & allowed	Indoor use, lateral installation possible & allowed
Outdoor use, central installation possible & allowed	Outdoor use, lateral installation possible & allowed	Ballasting of scaffolding, indoor, central installation 0 kg	Ballasting of scaffolding, indoor, lateral installation 0 kg	Ballasting of scaffolding, outdoor, central installation 0 kg
Ballasting of scaffolding, outdoor, lateral installation 0 kg	Business division MUNK Günzburger Steigtechnik	Order no. 154349	Price € 4,531.00	

## **Facts**

- Mobile scaffolding made of sturdy round aluminium tubing with welded frame parts
- Secured all around thanks to leading railing, can be assembled and dismantled from level to level
- All scaffolding parts are also available individually as spare or extension parts
- Stable and flexible thanks to folding outriggers



- Also ideal for wall mounting or moving in narrow aisles
- Four Ø 200 mm swivel castors with centric load application, locking mechanisms and spindles
- Aluminium toe boards and railing frames with integrated knee board as safety railing
- Can be set up and dismantled without tools thanks to push-fit connections and quick-release fasteners
- Easy to handle thanks to individual lightweight parts
- Different platform lengths available (1.80 / 2.45 / 3.0 m)
- Working heights up to 12.35 m
- GS-tested as per DIN EN 1004
- Load class/scaffolding group 3: 2.0 kN/m²

# Scope of supply

■ Push-fit frame, 0.75 m.: 2 x

■ Push-fit frame, 0.75 m.: 2 x

Safety railing for mobile scaffolding: 2 x

Platform with trapdoor: 1 x

■ Toe board front side: 2 x

■ Toe board long side: 2 x

■ Diagonal brace: 2 x

Horizontal strut: 2 x

Triangular outrigger: 4 x

Swivel castor with spindle: 4 x

Step-on bracket: 1 x

Instructions for assembly and use EN

1004-2 - de: 1 x

■ Push-fit frame, 0.75 m.: 2 x

# Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

RoHS

REACH



- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

# More product pictures



## Added value

## Safety at heights

- Optional protective assembly railing as safety railing during installation and removal
- Installation without the need of tools, uncomplicated and easy to handle
- Railing with integrated knee board and aluminium toe boards



## Highest quality

- User-friendly and robust design
- Low weight of the individual parts for easy handling
- Welded round tube frames for maximum stability
- All-round profiled rungs for safe ascent and descent



## Sturdy connection

- Automatically closing scaffolding claw with sophisticated geometry for a secure connection
- Innovative spring clip for plug-on frame no accidental loosening or losing possible
- Transverse and diagonal braces for high stability



## Modular kit system

- More than 180 variants are possible by combining different individual parts
- Flexible adaptations and extensions possible at any time
- Individual parts at the original part price
- Installation and removal without tools



#### Safe standing

- Adjustable outriggers with swing base or chassis bar ensure safe working depending on model
- Easy to handle
- Additional ballast weights required depending on application



## Everything at a glance

- Clip tray for clearly visible attachment of the necessary test documents to the scaffolding
- Weather and UV-resistant





#### Flexible basis

- Swivel castors with load centring in braked condition
- Height adjustment for level compensation
- Various sizes and designs



This product can be funded as part of the BG BAU work safety subsidies! Subsidy subject to conditions; for the latest information, please visit the homepage of BG BAU.

Our safety railing (SG) is a system-integrated side protection that minimises the risk of falling during assembly, conversion and dismantling, as well as when using working and protective scaffolding. With this technical protection you meet the highest safety standards and at the same time benefit from an attractive subsidy of up to 50% of the purchase costs (max. 100 euro per measure).

- ✓ For new mobile scaffolding: The safety railings are eligible as part of a complete working platform (including safety railings and frame parts).
- ✓ For existing scaffolding: Retrofits with compatible safety railings are possible.

All members of the BG BAU profit from this subsidy. This is intended to prevent accidents at work and improve ergonomics, especially on construction sites. All information from BG BAU can be found at: <a href="https://www.bgbau.de/service/angebote/arbeitsschutzpraemie">www.bgbau.de/service/angebote/arbeitsschutzpraemie</a>

A brief overview of the subsidy and an overview of our eligible products can be found on our website at <u>Knowledge</u>.



# Corporate certifications

# on sustainability criteria









