MUNK
Sicherheit. Made in Germany.



Order no.: 011305

Assembly platform with stairway access

Specification

Working height 3 m	Scaffolding length 2.68 m	Scaffolding width 802 mm	Scaffolding height 1.94 m	Platform width 600 mm
Platform length 1.8 m	Load capacity 1.5 kN/m2	Max. load capacity 200 kg	Transport dimensions (plus packaging) 2110 x 760 x 800 mm, 69.5 kg	Business division MUNK Günzburger Steigtechnik
Platform height 990 mm				

Facts

- Mobile scaffolding made of sturdy round aluminium tubing with welded frame parts
- Folding frame made of rectangular tube side-rails with self-locking hinges
- Fold-up stairs with 200 mm deep steps for a safe ascent
- Easy-to-operate lifting castors for moving to new locations
- Handrails on both sides, platform railings and a knee rail to ensure a high level of safety at work

- For narrow passages when assembled
- Space-saving during transport and storage, as it can be used as a trolley when folded up
- Four Ø 125 mm swivel castors with locking mechanisms
- Slip-resistant platform for secure standing
- Flexible use thanks to three different hook heights
- Delivered fully assembled
- Load class/scaffolding group 2: 1.5 kN/m²

Scope of supply

- Assembly platform: 1 x
- Fold-up stairs: 1 x
- Instructions for assembly and use EN 1004-2 - de: 1 x

More product pictures







Added value

Safety at heights

- Optional protective assembly railing as safety railing during installation and removal
- Installation without the need of tools, uncomplicated and easy to handle
- Railing with integrated knee board and aluminium toe boards



Modular kit system

- More than 180 variants are possible by combining different individual parts
- Flexible adaptations and extensions possible at any time
- Individual parts at the original part price
- Installation and removal without tools



Highest quality

- User-friendly and robust design
- Low weight of the individual parts for easy handling
- Welded round tube frames for maximum stability
- All-round profiled rungs for safe ascent and descent



Safe standing

- Adjustable outriggers with swing base or chassis bar ensure safe working depending on model
- Easy to handle
- Additional ballast weights required depending on application



Sturdy connection

- Automatically closing scaffolding claw with sophisticated geometry for a secure connection
- Innovative spring clip for plug-on frame – no accidental loosening or losing possible
- Transverse and diagonal braces for high stability



Everything at a glance

- Clip tray for clearly visible attachment of the necessary test documents to the scaffolding
- Weather and UV-resistant



Flexible basis

- Swivel castors with load centring in braked condition
- Height adjustment for level compensation
- Various sizes and designs



Sponsored by BG BAU

Specification subject to conditions; for the latest information please visit the BG BAU website (statutory accident insurance company for the construction and construction related services in Germany). Since 2014, the BG BAU has been promoting the purchase of platform ladders, step stools and ladder accessories with single-sided and double-sided access. All members of the BG BAU profit from this. This aims to prevent work accidents on building sites and improve ergonomic working practices. For more information by BG BAU, please visit:
www.bgbau.de/service/angebote/arbeitsschutzpraemie

A brief overview of the subsidy and an overview of our eligible products can be found on our website under know-how.

Corporate certifications

Standards for quality and sustainability









