MUNK
Sicherheit. Made in Germany.



Order no.: 115114

Folding scaffolding SG 0.75 x 1.80 m

Platform height [mm]

2080 | 3200

Specification

Working height 4.08 m	Scaffolding length 1.99 m	Scaffolding width 785 mm	Scaffolding height 3.35 m	Platform width 750 mm
Platform length 1.8 m	Load capacity 1.5 kN/m2	Transport dimensions (plus packaging) 1900 x 1100 x 800 mm, 74 kg	Indoor use, central installation possible & allowed	Indoor use, lateral installation not possible
Outdoor use, central installation possible & allowed	Outdoor use, lateral installation not possible	Ballasting of scaffolding, indoor, central installation 60 kg	Ballasting of scaffolding, outdoor, central installation 270 kg	Business division MUNK Günzburger Steigtechnik
Platform height 2.08 m				

Facts

- Mobile scaffolding made of sturdy round aluminium tubing with welded frame parts
- Secured all around thanks to leading railing, can be assembled and dismantled from level to level
- All scaffolding parts are also available individually as spare or extension parts
- Folding frame made of rectangular tube side-rails with self-locking hinges

- Space-saving transport and storage
- Four swivel castors, Ø 125 mm, with central load distribution and spindles for height adjustment
- Slip-resistant platform for secure standing
- Aluminium toe boards and railing frames with integrated knee board as safety railing (from platform height of 2.8 m and higher)
- Simple setup and removal without tools
- Different platform widths available (0.75 / 1.35 m)
- Platform lengths of 2.45 m and 3.0 m upon request
- Load class/scaffolding group 2: 1.5 kN/m²
- Additional side boards for intermediate platforms are available as an option for country-specific requirements (e.g. Austria and France)

Scope of supply

- Folding frame unit, 0.75 m: 1 x
- Safety railing for mobile scaffolding: 2 x
- Platform with trapdoor: 1 x
- Toe board front side: 2 x
- Toe board long side: 2 x
- Swivel castor with spindle: 4 x
- Instructions for assembly and use EN 1004-2 - de: 1 x
- Push-fit frame 75/112: 2 x

More product pictures



MUNK
Sicherheit. Made in Germany.

Added value

Safety at heights

- Optional protective assembly railing as safety railing during installation and removal
- Installation without the need of tools, uncomplicated and easy to handle
- Railing with integrated knee board and aluminium toe boards



Modular kit system

- More than 180 variants are possible by combining different individual parts
- Flexible adaptations and extensions possible at any time
- Individual parts at the original part price
- Installation and removal without tools



Highest quality

- User-friendly and robust design
- Low weight of the individual parts for easy handling
- Welded round tube frames for maximum stability
- All-round profiled rungs for safe ascent and descent



Safe standing

- Adjustable outriggers with swing base or chassis bar ensure safe working depending on model
- Easy to handle
- Additional ballast weights required depending on application



Sturdy connection

- Automatically closing scaffolding claw with sophisticated geometry for a secure connection
- Innovative spring clip for plug-on frame – no accidental loosening or losing possible
- Transverse and diagonal braces for high stability



Everything at a glance

- Clip tray for clearly visible attachment of the necessary test documents to the scaffolding
- Weather and UV-resistant



Flexible basis

- Swivel castors with load centring in braked condition
- Height adjustment for level compensation
- Various sizes and designs



This product can be funded as part of the BG BAU work safety subsidies! Subsidy subject to conditions; for the latest information, please visit the homepage of BG BAU.

Our safety railing (SG) is a system-integrated side protection that minimises the risk of falling during assembly, conversion and dismantling, as well as when using working and protective scaffolding. With this technical protection you meet the highest safety standards and at the same time benefit from an attractive subsidy of up to 50% of the purchase costs (max. 100 euro per measure).

✔ For new mobile scaffolding: The safety railings are eligible as part of a complete working platform (including safety railings and frame parts).

✔ For existing scaffolding: Retrofits with compatible safety railings are possible.

All members of the BG BAU profit from this subsidy. This is intended to prevent accidents at work and improve ergonomics, especially on construction sites. All information from BG BAU can be found at: www.bgbau.de/service/angebote/arbeitsschutzpraemie

A brief overview of the subsidy and an overview of our eligible products can be found on our website at Knowledge.

Corporate certifications

Standards for quality and sustainability









