

Order no.: 030296

## Push-fit handrail for rung/step spacing 280/263 mm



Length [mm]

1400 1960

### Specification

Product type <b>Accessories</b>	Length <b>1.4 m</b>	Width <b>138 mm</b>	Diameter <b>25 mm</b>	Weight <b>1.23 kg</b>
Transport dimensions <b>1461 x 190 x 138 mm, 1.23 kg</b>	Business division <b>MUNK Günzburger Steigtechnik</b>	Order no. <b>030296</b>	Price <b>€ 103.00</b>	

### Facts

- Handrail made of aluminium tube Ø 25 mm
- Suitable for ladders with rung spacing of 280 mm or step spacing of 263 mm
- For tool-free installation via ergonomic star handle
- Fastening via clamping mechanism in the step hole
- Can be mounted either on the right or left side of the ladder

## Scope of supply

- Handrail (enclosed separately): 1 x

## Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548



**Nachhaltigkeit**  
**EcoVadis**  
sustainable supply management  
CSR-Rating in Silber 2022

