MUNK
Sicherheit. Made in Germany.



Order no.: 600364

Stairs with 60° platform step width 600 mm

Number of steps

4	5	6	7	8	9	10	11	12
13	14	15	16					

Specification

Surface Aluminium corrugated	Number of steps/rungs 4 steps	Step width 600 mm	Height 2.07 m	Vertical height 970 mm
Base area 1.27 m	Business division MUNK Günzburger Steigtechnik	Transport dimensions (plus packaging) 2362 x 1070 x 750 mm, 22.6 kg	Order no. 600364	

Facts

- Fixed stairs with aluminium platform with inclination 60°
- Step and platform width: 600 mm
- Platform length: 460 mm
- Last step (depth: 225 mm) mounted at the same height as the platform (total tread area: 685 mm)
- Standard step and platform surface, grooved aluminium (R 11), optionally also available with other surfaces (see overview on right)
- Handrail and railing on one side, Ø 40 mm, with bolted connecting elements as standard (height: 1,100 mm) as standard

- Second handrail as per DIN EN ISO 14122-3 required and available at asurcharge
- Lower side-rail ends with robust foot brackets for floor-mounted installation
- Front side railing available at a surcharge
- Easy installation thanks to delivery in pre-assembled modules including assembly instructions
- An intermediate platform is required for stairs with a vertical height of 3,000 mm or more (at a surcharge)
- If no support surfaces or attachments are provided by the customer, a triangular console must be used for mounting
- Maximum load: 1.5 kN/m2, step load 150 kg, total load 300 kg
- Note: The standard version includes connecting parts of galvanised steel, which are suitable for indoor use. At a surcharge, they can also be made of stainless steel, which is recommended for outdoor use
- Manufactured in accordance with the DIN EN ISO 14122 series of European standards
- Not suitable for residential use according to DIN 18065
- This product is made to order and cannot be returned

Scope of supply

- Stair module: 1 x
- Handrail (enclosed separately): 1 x
- Garde-corps: 1 x
- Installation material: 1 x
- Assembly instructions: 1 x

More product pictures





Added value

Product configurator

Configuring, enquiring about and ordering individual products could not be easier with our product configurator for stairs, bridging steps and mobile platform stairs. Simply enter your required dimensions and versions step by step, and a rotating 3D model will appear in real time. To save your configuration and request a quotation requires a login which will be set up for you by our Sales team.



Handrail and railing

- Handrail on one side as standard (height: 1,100 mm)
- Depending on the application, a second handrail or front side railing are available
- At an additional charge, plug-in pockets with quick-release fasteners for easy removal of railing and handrail and railing with filler rods or coverings available



Safety railing in the access area

- Safety doors with fixed sizes or telescopic
- Alternative when, for example, a safety door is not possible due to structural conditions. Safety barriers or safety rope are also available



Top surface

The total tread area depends on the platform length selected. This is made up of the platform length plus the depth of the last step(s) (for bridging steps times two), as these are mounted at the same height



Different widths

- Steps and platforms are available in standard widths of 600, 800 and 1,000 mm
- Special sizes available on request



Simple installation

- Delivery in pre-assembled modules including assembly instructions
- Quick assembly thanks to screw connections for struts and support parts as well as plug-in pockets for railings

This is what distinguishes our stairs and bridging steps

- Individual planning and production by Günzburger Steigtechnik experts in accordance with customer specifications
- Inclinations of 45° and 60° and widths of 600, 800 and 1,000 mm as standard, special dimensions and deviating inclinations available on request
- Standard step and platform design in grooved aluminium (R 9), optionally also in steel grating (R 12), aluminium grating (R 13), perforated steel cover (R 13), perforated aluminium cover (R 13) or with corundum coating (R 13)
- Handrail and railing on one side made of Ø 40 mm tubes with bolted connecting elements as standard (height: 1,100 mm). Handrail and railing are available on both sides at a surcharge, as well as plug-in pockets with quick-release fasteners for easy removal of the railing and railings with filler rods or covers
- Side-rails made of strong aluminium sections. The upper end is equipped with support angles, the lower end with plastic shoes
- Depending on step width and vertical height, central supports in the form of consoles or support frames, and intermediate platforms are sometimes required (at an additional charge)
- Maximum load: 1.5 kN / m², step load 150 kg, total load 300 kg
- Foot bracket for fixing to the ground and various undercarriage variants for mobile use optionally available as accessories
- The delivery from the factory is made in pre-assembled modules for quick and simple assembly in accordance with the enclosed assembly instructions

MUNK
Sicherheit. Made in Germany.

Corporate certifications

Standards for quality and sustainability

Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022