MUNK
Sicherheit. Made in Germany.



Order no.: 040694

2-section step rope-extension ladder with nivello stabiliser and clip-step R13

Number of steps

2x12

Specification

Working height 6.5 m	Step design Steps	Number of steps/rungs 2x 12 steps	Step depth 80 mm	Step/Rung distance 263 mm
Retracted length 3.62 m	Extended length 6.42 m	Length of ladder sections 3.62 m	Inclination 70 °	Outer width 420 mm
Stabiliser width 1.2 m	Depth of side-rails 85 mm	Width of side-rails 25 mm	Design type To lean against | 2-part	Transport dimensions (plus packaging) 3500 x 420 x 200 mm, 25 kg
Business division MUNK Günzburger Steigtechnik	Order no. 040694			

Facts

- Step rope-extension ladder, aluminium
- Complies with standard DIN EN 131-2 and TRBS 2121 Part 2
- Stable rectangular tube side-rails
- clip-step R13 step padding for certified non-slip protection

- Grooved steps with a depth of 80 mm R10
- 4-fold edged step-to-side-rail connection
- Galvanised steel fittings
- Upper ladder with wall wheels, without cross-tube, therefore suitable for access
- Convenient height adjustment from step to step, thanks to rope pulley with plastic rope arranged on the left side
- Lower ladder with nivello® stabiliser for extra stability and safe ascent (enclosed separately)
- Self-locking double locking hook
- ‘Roll-bar’ retrofit kit for enhanced ergonomics, available as an accessory
- Step spacing: 263 mm
- Ladder width: 420 mm (without stabiliser)
- Ladder inclination: 70°
- Maximum load: 150 kg
- Attention! All accessory attachments such as handrails or exit rails can only be fitted to the ladder when the ladder is in the extended position and is no longer extended or retracted.
- Mounting of hooks not possible
- Please note: Wear and tear of the corundum grit caused by use is typical of this material. Individual particles may also become dislodged during use.

Scope of supply

- Ladder: 1 x
- Stabiliser (enclosed separately): 1 x
- Instructions for use and operation: 1 x

More product pictures









Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Optimum and smooth operation, thanks to easily accessible elements

- Simple height adjustment from rung to rung or from step to step
- Wall wheels on the upper part (from 14 rungs or more)
- Fittings with sliding guides
- Smooth-running rope pulley



Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



nivello® stabiliser

Extra safe, standards-compliant ascent for straight ladders over 3.0 m

- Extra wide stabiliser for even greater stability
- nivello® ladder shoes with patented 2-axis inclination technology, integrated work angle check and exchangeable foot plates
- Individually available as spare part



roll-bar retrofit kit

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down



The movable ladder shoe sets new standards in stability

Learn more



MUNK
Sicherheit. Made in Germany.

Corporate certifications

Standards for quality and sustainability

Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022