MUNK
Sicherheit. Made in Germany.



Order no.: 022314

3-section rung rope-extension ladder without stabiliser

Number of rungs

3x14 | 3x16 | 3x18

Specification

Working height 10.8 m	Step design Rungs	Number of steps/rungs 3x 14 rungs	Step/Rung height 30 mm	Step depth 30 mm
Step/Rung distance 280 mm	Retracted length 4.1 m	Extended length 9.7 m	Outer width 470 mm	Depth of side-rails 98 mm
Width of side-rails 25 mm	Design type To lean against | 3-part	Transport dimensions (plus packaging) 4190 x 500 x 275 mm, 43 kg	Business division MUNK Günzburger Steigtechnik	Order no. 022314

Facts

- Rung rope-extension ladder made of aluminium
- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm, Slip resistance class R10
- 4-fold edged rung-to-side-rail connection
- Convenient height adjustment from rung to rung thanks to two pulleys with plastic cable
- Automatically acting locking hooks, middle and upper part adjusted separately

- Upper ladder with wall wheels
- Corrosion-resistant guide fixtures with sliding guides
- Rung distance: 280 mm
- Ladder width: 470 mm (without stabiliser)
- Maximum load: 150 kg
- nivello® ladder shoes with patented 2-axis inclination technology
- Note: Straight ladders over 3.0 m can be used without a stabiliser only when they are used exclusively for their intended purpose (e.g. permanently installed, fitted with hooks, fastened with a belt)
- Note: In accordance with standards, the attached push-up extension ladder section cannot be separated from the ladder with lengths over 3.0 m

Scope of supply

- Ladder: 1 x
- Instructions for use and operation: 1 x

More product pictures









Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Optimum and smooth operation, thanks to easily accessible elements

- Simple height adjustment from rung to rung or from step to step
- Wall wheels on the upper part (from 14 rungs or more)
- Fittings with sliding guides
- Smooth-running rope pulley



Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



Retrofit stabiliser

Safe, standards-compliant ascent

- For retrofitting existing ladders with ladder lengths over 3.0 m in compliance with standards
- Non-slip ladder shoes
- Available in different widths



The movable ladder shoe sets new standards in stability

Learn more



MUNK
Sicherheit. Made in Germany.

Corporate certifications

Standards for quality and sustainability

Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022