MUNK
Sicherheit. Made in Germany.



Order no.: 036108

2-section rung push-up extension ladder made of glass-fibre reinforced plastic without stabiliser

Number of rungs

2x8 | 2x10 | 2x12

Specification

Working height 5.2 m	Step design Rungs	Number of steps/rungs 2x 8 rungs	Step/Rung height 29 mm	Step depth 28 mm
Step/Rung distance 280 mm	Retracted length 2.5 m	Extended length 4.18 m	Outer width 420 mm	Depth of side-rails 73 mm
Width of side-rails 25 mm	Design type To lean against | 2-part	Transport dimensions (plus packaging) 2480 x 428 x 143 mm, 15.5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 036108

Facts

- Rung push-up extension ladder made of glass-fibre reinforced plastic
- Side-rails and rungs made of reinforced fibre glass plastic profiles
- Rectangular rungs grooved on both sides, 28 x 29 mm
- By using the metal suspension step, the insulation voltage is reduced to 1,000 V
- High-strength rung-to-side-rail connection

- Galvanised steel fittings
- Easy height adjustment from rung to rung
- Upper ladder from size 2x12 rungs with wall castors
- Corrosion-resistant guide fixtures
- Upper ladders up to 3.0 m with nivello® ladder shoes
- Rung distance: 280 mm
- Ladder width: 420 mm (without stabiliser)
- nivello® ladder shoes with patented 2-axis inclination technology
- Maximum load: 150 kg
- Suitable for working near or on live parts
- Tested in accordance with DIN EN 61478:2002 + DIN EN 61478/A1:2004, Section 6.5.1, Category 1: 24,500 V
- Note: In accordance with standards, the attached push-up extension ladder section cannot be separated from the ladder with lengths over 3.0 m
- Note: Straight ladders over 3.0 m can be used without a stabiliser only when they are used exclusively for their intended purpose (e.g. permanently installed, fitted with hooks, fastened with a belt)

Scope of supply

- Ladder: 1 x
- Instructions for use and operation: 1 x

More product pictures







Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Optimum and smooth operation, thanks to easily accessible elements

- Simple height adjustment from rung to rung or from step to step
- Wall wheels on the upper part (from 14 rungs or more)
- Fittings with sliding guides
- Smooth-running rope pulley



Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



The movable ladder shoe sets new standards in stability

Learn more



Fiberglass

Ladders made of GFRP offer the perfect properties for special challenges. Find out what makes GFRP such a special material, how we use it for ladders and where these ladders are used.



MUNK
Sicherheit. Made in Germany.

Corporate certifications

Standards for quality and sustainability

Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022