



Order no.: 040103

Single-sided stepladder



Number of steps



14

Specification

Working height 2.7 m	Step design Steps	Number of steps/rungs 3 steps	Platform included as step Yes	Step depth 80 mm
Step/Rung distance 235 mm	Type of non-slip protection Aluminium corrugated	Height 1.34 m	Platform height 670 mm	Base spread 700 mm
Inclination 70 °	Lower outer width 470 mm	Depth of side-rails 73 mm	Depth of side-rails, support 58 mm	Width of side-rails 25 mm
Max. load capacity 150 kg	Design type Freestanding Single-sided access	Weight 5.5 kg	Transport dimensions 1434 x 461 x 164 mm, 5.5 kg	Business division MUNK Günzburger Steigtechnik
Order no. 040103	Price € 210.00			

Facts

- Stepladder made of aluminium
- Stable rectangular tube side-rails
- 80 mm deep grooved steps and large platform



- 4-fold edged step-to-side-rail connection
- Conical side-rail guide for safe stance
- nivello® ladder shoes with patented 2-axis inclination technology
- ergo-pad® grip area with clamping mechanism
- 'safe-cap' ladder joint
- Practical storage tray with integrated hooks and tool holders
- From seven steps or more: Spreader lock with two high-strength polyester straps
- Step spacing: 235 mm
- Ladder inclination: 70°
- Available with and without step padding
- Maximum load: 150 kg

Scope of supply

Ladder: 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany



- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Ladder joint safe-cap

- Smooth ladder joint with large contact surface and sturdy plastic protective cap
- The 6 rivets and thicker wall thickness provide for greater stability and protection at this sensitive point on the ladder, increasing its service life
- The safe-cap protects the ladder when in use, when loading and storing, as well as the contact surfaces, walls, truck loading areas and the joint itself

ergo-pad® grip area

For easier and more ergonomic handling at the optimum carrying point



Storage tray

- For the practical storage of small parts
- Made from high-quality plastic
- Partly with integrated hooks and tool holders
- Different versions, depending on the ladder model



The movable ladder shoe sets new standards in stability





Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on <u>TRBS 2121 Part 2</u> has been summarised on our Service page
- Read our <u>tips and tricks</u> on how to calculate working height



Certificates

17KFP0689-04 - Test Certificate "Bauart geprüft" Valid in	
DIN EN 131-3:2007 EK5-AK1 17- 02:2017 DIN EN 131-1:2016 DIN EN 131-2:2017 PAK- ANFORDERUNG FÜR GS - ABSCHNITT 3.1(PAH- REQUIREMENT FOR GS - CL. 3.1) AFPS GS 2014:01 PAK	



Corporate certifications

on sustainability criteria



