MUNK
Sicherheit. Made in Germany.



Order no.: 040103

Single-sided stepladder

Number of steps

3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 12 | 14

Specification

Working height 2.7 m	Step design Steps	Number of steps/rungs 3 steps	Platform included as step Yes	Step depth 80 mm
Step/Rung distance 235 mm	Type of non-slip protection Aluminium corrugated	Height 1.34 m	Platform height 670 mm	Base spread 700 mm
Inclination 70 °	Lower outer width 470 mm	Depth of side-rails 73 mm	Depth of side-rails, support 58 mm	Width of side-rails 25 mm
Max. load capacity 150 kg	Design type Freestanding | Single-sided access	Transport dimensions (plus packaging) 1434 x 461 x 164 mm, 5.5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 040103

Facts

- Stepladder made of aluminium
- Stable rectangular tube side-rails
- 80 mm deep, ribbed steps R10
- 4-fold edged step-to-side-rail connection
- Conical side-rail guide for safe stance

- nivello® ladder shoes with patented 2-axis inclination technology
- ergo-pad® grip area with clamping mechanism
- 'safe-cap' ladder joint
- Practical storage tray with integrated hooks and tool holders
- From seven steps or more: Spreader lock with two high-strength polyester straps
- Step spacing: 235 mm
- Ladder inclination: 70°
- Available with and without step padding
- Maximum load: 150 kg

Scope of supply

- Ladder: 1 x

More product pictures







Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Ladder joint safe-cap

- Smooth ladder joint with large contact surface and sturdy plastic protective cap
- The 6 rivets and thicker wall thickness provide for greater stability and protection at this sensitive point on the ladder, increasing its service life
- The safe-cap protects the ladder when in use, when loading and storing, as well as the contact surfaces, walls, truck loading areas and the joint itself



ergo-pad® grip area

For easier and more ergonomic handling at the optimum carrying point



Storage tray

- For the practical storage of small parts
- Made from high-quality plastic
- Partly with integrated hooks and tool holders
- Different versions, depending on the ladder model




The movable ladder shoe sets new standards in stability

Learn more



Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on TRBS 2121 Part 2 has been summarised on our Service page
- Read our tips and tricks on how to calculate working height



Certificates



25KFP0048-01 - Test Certificate "Bauart geprüft"

Valid in

DIN EN 131-3:2018
EK5/AK1 17-02.4:2021
DIN EN 131-1:2019
DIN EN 131-2:2017
PAK-ANFORDERUNG FÜR GS (PAH REQUIREMENT FOR GS) AFPS GS 2019:01 PAK

MUNK
Sicherheit. Made in Germany.

Corporate certifications

Standards for quality and sustainability

Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022