



Order no.: 060018

Wall anchor, rigid, galvanised steel

Wall clearance [mm]

150

Specification

Suitable for Shaft ladders	Wall distance 150 mm	Weight 0.42 kg	Transport dimensions 179 x 73 x 40 mm, 0.42 kg	Business division MUNK Günzburger Steigtechnik
Order no. 060018	Price € 11.00			

Facts

- Wall anchor, rigid
- For shaft ladders
- Galvanised steel
- Note: 2 sets (=4 pcs.) of wall anchors are required for ladders with 4–9 rungs, 3 sets (= 6 pcs.) of wall anchors for ladders with 10–15 rungs, and 5 sets (=10 pcs.) of wall anchors for ladders with 16–24 rungs



- 1 set = 2 pieces (1x right, 1x left). Wall plugs and bolts are to be used to fasten the ladder to the shaft rather than nuts and screwed bolts when their suitability has been verified at the place where the ladder is used. They have to be selected in accordance with the force acting on the ladder anchoring point as stated by the manufacturer.
- Dowels and screws for attachment to the wall are not included in the delivery. Please contact well-known dowel suppliers for information.

Scope of supply

■ Wall anchor: 1 x

Assembly instructions: 1 x

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard,
 small amounts of plastic
- No health hazards for the users



More product pictures



Corporate certifications

on sustainability criteria









