



Order no.: 063004

**Shaft ladder, V4A**  
stainless steel, 400 mm  
clear width

Number of rungs

- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11
- 12
- 13
- 14
- 15

## Specification

Clear width 400 mm	Ladder length 1.12 m	Number of steps/rungs 4 rungs	Step depth 30 mm	Depth of side-rails 50 mm
Width of side-rails 20 mm	Outer width 440 mm	Max. load capacity 150 kg	Material Stainless steel V4A	Weight 5.5 kg
Transport dimensions 1120 x 440 x 50 mm, 5.5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 063004	Price € 242.00	

## Facts

- Cured and passivated
- Clear width 400 mm
- Rectangular tube side-rails, 50 x 20 mm
- Non-slip perforated rungs
- Various wall anchors available as accessories

## Scope of supply

- Ladder: 1 x

## Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---

## Added value

---

### Rational modular principle

- Shaft ladders in two widths and various lengths offer the right solution for every project
- Ideal for sewage treatment plants, landfills, retention basins, pump shafts, etc.
- Each individual component in the modular kit system meets the same quality and efficiency requirements
- Use of fall protection with wide design possible



### Mounting and fastening

- Quick and easy installation of the shaft ladders thanks to the optimised installation system
- Adjustable wall anchors for complex projects additionally facilitate installation
- Suitable accessories available for the different material versions



### Highest quality

- Stable rectangular tube side-rails
- High-strength rung-to-side-rail connection
- Non-slip perforated rungs



### Various material versions

- Depending on the application, shaft ladders made of steel, stainless steel and reinforced fibre glass are available
- Wall anchors and accessories are also available in several materials



### Entry aids

- Different variants in accordance with DIN standards and German Social Accident Insurance (DGUV) regulations for safe entry and exit
- Available in various materials to match the ladders



## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

