

Order no.: 110007

Wooden folding ladder DIN EN 1147



Specification

Intended use Access	Ladder length 3 m	Setting angle 70 °	Clear width between rungs 265 mm	Outer width 90 mm
Ladder feet Steel point	Depth of side-rails 60 mm	Width of side-rails 45 mm	Step/Rung height 34 mm	Step depth 20 mm
Number of steps/rungs 9 rungs	Step/Rung distance 300 mm	Max. load capacity 150 kg	Persons max. 1	Material Wood
Weight 9.5 kg	Transport dimensions 3267 x 90 x 60 mm, 9.5 kg	Business division MUNK Rettungstechnik	Order no. 110007	

Facts

- Wooden folding ladder
- Access ladder compliant with DIN EN 1147
- Collapsible design
- Side-rails made of finger-jointed pine or knot-free Oregon pine
- 9 rungs made of knot-free ash

- Wooden parts painted in colourless varnish
- End fixtures for insertion
- Corrosion-resistant fixtures made of galvanised steel
- Permissible load: 108 kg / 1 person

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Corporate certifications

on sustainability criteria



Management System
ISO 9001:2015
ISO 14001:2015
www.tuv.com
ID 9108612548

