MUNK
Sicherheit. Made in Germany.



Order no.: 115301

# Folding scaffolding

Platform width [mm]

750 | 1350

## Specification

| | | | | |
|---|---|---|---|---|
| Working height<br>3 m | Scaffolding length<br>1.88 m | Scaffolding width<br>841 mm | Scaffolding height<br>1.72 m | Platform width<br>750 mm |
| Platform length<br>1.8 m | Load capacity<br>1.5 kN/m2 | Transport dimensions (plus packaging)<br>1900 x 1100 x 500 mm, 37 kg | Indoor use, central installation<br>possible & allowed | Outdoor use, central installation<br>possible & allowed |
| Ballasting of scaffolding, indoor, central installation<br>0 kg | Ballasting of scaffolding, outdoor, central installation<br>0 kg | Business division<br>MUNK Günzburger Steigtechnik | Platform height<br>990 mm | |

## Facts

- Mobile scaffolding made of sturdy round aluminium tubing with welded frame parts
- Folding frame made of rectangular tube side-rails with self-locking hinges
- Fits through doors when assembled (item no. 115301)
- Space-saving transport and storage
- Four Ø 125 mm swivel castors with locking mechanisms
- Slip-resistant platform for secure standing

- Delivered in assemblies. Once assembled, the scaffolding can be quickly set up and dismantled without tools
- Different platform widths available (0.75 / 1.35 m)
- Type-tested
- Load class/scaffolding group 2: 1.5 kN/m²
- Additional side boards for intermediate platforms are available as an option for country-specific requirements (e.g. Austria and France)

## Scope of supply

- Folding frame unit with swivel castors: 1 x
- Platform without flap: 1 x
- Instructions for assembly and use EN 1004-2 - de: 1 x

## More product pictures



MUNK
Sicherheit. Made in Germany.

## Added value

### Safety at heights

- Optional protective assembly railing as safety railing during installation and removal
- Installation without the need of tools, uncomplicated and easy to handle
- Railing with integrated knee board and aluminium toe boards



### Modular kit system

- More than 180 variants are possible by combining different individual parts
- Flexible adaptations and extensions possible at any time
- Individual parts at the original part price
- Installation and removal without tools



### Highest quality

- User-friendly and robust design
- Low weight of the individual parts for easy handling
- Welded round tube frames for maximum stability
- All-round profiled rungs for safe ascent and descent




### Safe standing

- Adjustable outriggers with swing base or chassis bar ensure safe working depending on model
- Easy to handle
- Additional ballast weights required depending on application



### Sturdy connection

- Automatically closing scaffolding claw with sophisticated geometry for a secure connection
- Innovative spring clip for plug-on frame – no accidental loosening or losing possible
- Transverse and diagonal braces for high stability



### Everything at a glance

- Clip tray for clearly visible attachment of the necessary test documents to the scaffolding
- Weather and UV-resistant



Flexible basis

- Swivel castors with load centring in braked condition
- Height adjustment for level compensation
- Various sizes and designs



Expand your scaffolding with a safety railing (SG) and ensure reliable protection at work thanks to the system-integrated side protection! The retrofit reduces the risk of falling and enables the BG BAU work safety subsidy to be paid for up to 50% of the purchase costs (max. 100 euro per measure).

✔ Suitable for this product: Compatible SG safety railings offer effective side protection and are easy to retrofit.

All members of the BG BAU profit from this subsidy. This is intended to prevent accidents at work and improve ergonomics, especially on construction sites. All information from BG BAU can be found at: www.bgbau.de/service/angebote/arbeitsschutzpraemie

A brief overview of the subsidy and an overview of our eligible products can be found on our website at Knowledge.

# Corporate certifications

## Standards for quality and sustainability













