MUNK
Sicherheit. Made in Germany.



Order no.: 022414

# 3-section rung rope-extension ladder with nivello® stabiliser

Number of rungs

3x14 | 3x16 | 3x18

## Specification

| | | | | |
|---|---|---|---|---|
| Working height<br>10.8 m | Step design<br>Rungs | Number of steps/rungs<br>3x 14 rungs | Step/Rung height<br>30 mm | Step depth<br>30 mm |
| Step/Rung distance<br>280 mm | Retracted length<br>4.1 m | Extended length<br>9.7 m | Outer width<br>470 mm | Stabiliser width<br>1.2 m |
| Depth of side-rails<br>98 mm | Width of side-rails<br>25 mm | Design type<br>To lean against \| 3-part | Transport dimensions (plus packaging)<br>4175 x 500 x 255 mm, 45.7 kg | Business division<br>MUNK Günzburger Steigtechnik |
| Order no.<br>022414 | | | | |

## Facts

- Rung rope-extension ladder made of aluminium
- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm, Slip resistance class R10
- 4-fold edged rung-to-side-rail connection

- Convenient height adjustment from rung to rung thanks to two pulleys with plastic cable
- Automatically acting locking hooks, middle and upper part adjusted separately
- Upper ladder with wall wheels
- Corrosion-resistant guide fixtures with sliding guides
- Rung distance: 280 mm
- Ladder width: 470 mm (without stabiliser)
- Maximum load: 150 kg
- nivello® stabiliser with optimum width for the selected product, ensuring an extra safe stance and ascent thanks to nivello® ladder shoes with 2-axis inclination technology, working angle check and exchangeable foot plates. The stabiliser is enclosed separately and is screwed to the lower end of the rail in two places
- Note: In accordance with standards, the attached push-up extension ladder section cannot be separated from the ladder with lengths over 3.0 m

## Scope of supply

- Ladder: 1 x
- Stabiliser (enclosed separately): 1 x
- Instructions for use and operation: 1 x

## More product pictures







## Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Optimum and smooth operation, thanks to easily accessible elements

- Simple height adjustment from rung to rung or from step to step
- Wall wheels on the upper part (from 14 rungs or more)
- Fittings with sliding guides
- Smooth-running rope pulley



Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



roll-bar retrofit kit

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down



The movable ladder shoe sets new standards in stability

Learn more



# Corporate certifications

## Standards for quality and sustainability













