MUNK
Sicherheit. Made in Germany.



Order no.: 120006

# Mobile container breathing apparatus

Type

- **Breathing apparatus**
- Breathing apparatus and spare bottles
- Breathing apparatus boxes
- Breathing apparatus boxes and spare bottles

## Specification

| | | | | |
|---|---|---|---|---|
| Product type<br>Breathing apparatus | Length<br>1.2 m | Width<br>800 mm | Height<br>1.19 m | Height up to top edge of extension<br>1.19 m |
| Max. load capacity<br>500 kg | Castor diameter<br>200 mm | Braking system<br>Standard | Number of levels<br>3 | Number of breathing apparatuses<br>6 |
| Number of breathing apparatus cylinders<br>0 | Transport dimensions (plus packaging)<br>1200 x 800 x 1185 mm, 142 kg | Business division<br>MUNK Rettungstechnik | Order no.<br>120006 | |

## Facts

- Mobile container with "standard" undercarriage
- For the safe and protected transport of six breathing apparatuses (single canister) and six respirator masks with filters and regulators
- Closed structure made of 12 mm wooden platform boards
- Division into three storage levels with closing flaps
- Including three storage trays made of aluminium with handle (L x W x H: (673 x 222 x 230 mm))



We reserve the right to make technical changes and price changes.

- Compartment for breathing apparatus (L x W x H 730 x 410 x 270 mm)
- Further sizes and versions available on request
- Optionally also available with "Quadro" and "Quadro Light" undercarriage
- Scope of delivery without equipment items
- Series production quality equipment
- Stable and durable construction made of high-strength aluminium sections
- Platforms made of weatherproof wooden platform boards
- Ergo-Glow-Grip control unit – Continuous handlebar, oval-shaped for intuitive operation. Photoluminescent controls charge via UV radiation – for full functionality and safety even in the dark
- Robust and smooth-running actuating mechanism via flexible Bowden cable
- Two ball bearing castors Ø 200 mm with central wheel slewing arrestor for optimum handling
- Two ball bearing fixed castors Ø 200 mm with drum brake and dead man's function, resistant to dust, moisture and oil
- Foot-operated parking brake
- DEKRA certificate: Load securing in connection with load securing system

## Scope of supply

- Mobile container: 1 x

## More product pictures







## Added value

- The following equipment features are included as standard with every mobile container in the "Standard" assortment
- Body made of high-strength aluminium screw channel profile Connection of the profiles via stable, crossover corner screw connections – no welding!
- Markings for good visibility in the dark
- 2 fixed castors Ø 200 mm with internal drum brake and dead man's function
- 2 swivel castors Ø 200 mm with directional arrestors and central wheel and slewing arrestors
- Galvanised steel foot parking brake for swivel castors
- Operating control with ergonomic and continuous handle bars with SoftGrip coating
- Robust and smooth-running actuating mechanism via high-quality stainless steel Bowden cable

## Certificates




226/35527/703550/18
0553410 - Load securing certificate

Valid in

VDI 2700:2004
DIN EN 12195:2011
DIN EN 12642:2017

MUNK
Sicherheit. Made in Germany.

# Corporate certifications

## Standards for quality and sustainability

Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022