



Order no.: 033510

## Double-sided rung ladder suitable for stairs



Number of rungs

**2x5**

2x6

2x7

2x8

### Specification

Working height 3.6 m	Step design Rungs	Number of steps/rungs 2x 5 rungs	Step/Rung height 30 mm	Step depth 30 mm
Step/Rung distance 280 mm	Type of non-slip protection Aluminium corrugated	Height 1.47 m	Ladder length 1.5 m	Base spread 1.08 m
Base spread max. extended 1.56 m	Inclination 70 °	Lower outer width, ascent unit extended 640 mm	Lower outer width, ladder retracted 600 mm	Lower outer width, support part extended 700 mm
Max. adjustment range on the ascent unit 400 mm	Max. adjustment range on the support part 1 m	Depth of side-rails 58 mm	Width of side-rails 25 mm	Max. load capacity 150 kg
Design type Freestanding   Double-sided access   Suitable for stairs	Weight 11 kg	Transport dimensions 1535 x 590 x 225 mm, 11 kg	Business division MUNK Günzburger Steigtechnik	Order no. 033510
Price € 668.00				

### Facts

- Double-sided rung ladder made of aluminium

- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection
- Conical side-rail guide for safe stance
- nivello® ladder shoes with patented 2-axis inclination technology
- Solid, galvanised steel hinges with screw attachment
- Plastic end caps on upper side-rail end
- Spreader lock with two high-strength polyester straps
- Transport securing straps
- Rung distance: 280 mm
- Four bar extensions with solid sliding guide and ergonomic star handle
- Adjustment range on the ascent section: max. 400 mm
- Adjustment range on the support section: max. 1,000 mm
- Maximum load: 150 kg

### Scope of supply

- Ladder: 1 x

### Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct

- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures

---

## Added value

---

### Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories




The movable ladder shoe sets new standards in stability

[Learn more](#)




### Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)




## Certificates

---



17KFP1657-02 -  
Test Certificate  
"Bauart geprüft"

Valid in



DIN EN 131-3:2007  
PAK-  
ANFORDERUNG  
FÜR GS -  
ABSCHNITT  
3.1(PAH-  
REQUIREMENT  
FOR GS - CL. 3.1)  
AFPS GS 2014:01  
PAK  
EK5-AK1 17-  
02:2017  
DIN EN 131-1:2016  
DIN EN 131-2:2017

## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548



**Nachhaltigkeit**  
**EcoVadis**  
sustainable supply management  
CSR-Rating in Silber 2022

