



Order no.: 062960

# Intermediate platform, folding

Material

Aluminium uncoated

Anodised aluminium

Stainless steel

Galvanised steel

# Specification

Material Aluminium	Weight 4.5 kg	Transport dimensions 680 x 750 x 180 mm, 4.5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 062960
Price € 487.00				

# **Facts**

- Comfortable footing area for stability and safety
- Can be used as a resting platform for singleflight vertical ladders. Fastening via an additional bracket on the back protection. One bracket included in the scope of delivery.
- High load capacity for demanding applications
- Dimensions approx. 600 x 300 mm



# Scope of supply

■ Platform: 1 x

Installation material: 1 x

### Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

#### More product pictures



#### Added value

#### Optimum planning

- Practical planning aids (available as <u>Downloads</u>) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning



#### All fixed ladders / vertical ladders at a glance:

- Single-flight vertical ladders in accordance with DIN 18799-1/-3, DIN 14094-1 and DIN EN ISO 14122-4 (depending on the choice of standard and the situation on site at the exit, additional components such as exit steps, railings and safety doors may be required)
- DIN 18799-1: Stationary multiple-flight vertical ladders on buildings
- DIN 14094-1: Multiple-flight emergency ladder systems (emergency ladders)
- DIN EN ISO 14122-4: Stationary multiple-flight vertical ladders on machinery



# Corporate certifications

# on sustainability criteria









