MUNK
Sicherheit. Made in Germany.



Order no.: 061264

Ladder section anodised aluminium

Length [mm]

1960 | 2800 | 3640

Specification

Length 1.96 m	Outer width 520 mm	Step width 470 mm	Step/Rung height 30 mm	Step depth 30 mm
Step/Rung distance 280 mm	Number of steps/rungs 7 rungs	Depth of side-rails 60 mm	Max. load capacity 150 kg	Non-slip class R11
Material Anodised aluminium	Transport dimensions (plus packaging) 1955 x 520 x 60 mm, 3.5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 061264	Spare part for article no. 500125
Spare part for article no. 500100				

Facts

- Ladder width 520 mm
- Rung distance: 280 mm
- Side-rail dimensions: 60 x 25 mm
- Dimension of rungs: 30 x 30 mm

We reserve the right to make technical changes and price changes.

- Rung design: with anodised aluminium and bright aluminium grooved rungs, with galvanised steel and stainless steel perforated rungs

Scope of supply

- Ladder section: 1 x

More product pictures



Added value

Optimum planning

- Practical planning aids (available as Downloads) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning



MUNK
Sicherheit. Made in Germany.

Corporate certifications

Standards for quality and sustainability

Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022