MUNK
Sicherheit. Made in Germany.



Order no.: 116101

Scaling ladder lower section ÖNORM F 4047

Specification

Intended use Rettung	Ladder length 2.7 m	Setting angle 70 °	Clear width between rungs 245 mm	Outer width 483 mm
Ladder feet Leiterschuh	Depth of side-rails 74 mm	Width of side-rails 35 mm	Step/Rung height 28 mm	Step depth 29 mm
Number of steps/rungs 9 rungs	Step/Rung distance 273 mm	Max. load capacity 216 kg	Persons max. 2	Material Aluminium
Transport dimensions (plus packaging) 2660 x 484 x 85 mm, 7.5 kg	Business division MUNK Rettungstechnik	Order no. 116101		

Facts

- Ladder section A with continuous rungs
- Can be used individually or as the bottom section of a ladder
- Rescue ladder, made of aluminium, compliant with ÖNORM F4047
- Secure push-fit connections with spring-loaded locking pin

- 4-fold edged rung-to-side-rail connection
- Conical side-rail guide for safe stance
- Corrosion-resistant fixtures made of galvanised steel
- Non-slip and replaceable ladder shoes
- Upper ladder with box profile rung made of aluminium chequered plate
- Permissible load: 2 persons

More product pictures









MUNK
Sicherheit. Made in Germany.

Corporate certifications

Standards for quality and sustainability

Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022