MUNK
Sicherheit. Made in Germany.



Order no.: 116102

Scaling ladder upper section ÖNORM F 4047

Specification

Intended use Rettung	Ladder length 2.7 m	Setting angle 70 °	Clear width between rungs 245 mm	Outer width 483 mm
Ladder feet Leiterschuh	Depth of side-rails 74 mm	Width of side-rails 35 mm	Step/Rung height 28 mm	Step depth 29 mm
Number of steps/rungs 7 rungs	Step/Rung distance 273 mm	Max. load capacity 216 kg	Persons max. 2	Material Aluminium
Transport dimensions (plus packaging) 2660 x 577 x 85 mm, 6 kg	Business division MUNK Rettungstechnik	Order no. 116102		

Facts

- Ladder section B with recessed rung guide
- To assemble a multi-piece plug-in cable set
- Can also be used individually or as the bottom rung with the insert
- Rescue ladder, made of aluminium, compliant with ÖNORM F4047

We reserve the right to make technical changes and price changes.

- Secure push-fit connections with spring-loaded locking pin
- 4-fold edged rung-to-side-rail connection
- Conical side-rail guide for safe stance
- Corrosion-resistant fixtures made of galvanised steel
- Non-slip and replaceable ladder shoes
- Upper ladder with box profile rung made of aluminium chequered plate
- Permissible load: 2 persons

More product pictures









MUNK
Sicherheit. Made in Germany.

Corporate certifications

Standards for quality and sustainability

Nachhaltigkeit
EcoVadis
sustainable supply management
CSR-Rating in Silber 2022