

Order no.: 032013

## Telescopic ladder 4-section without stabiliser



Number of rungs

4x3

4x4

4x5

4x6

### Specification

Working height min. 3.05 m	Working height max. 4.2 m	Number of steps/rungs 4x 3 rungs	Step/Rung height 30 mm	Step depth 30 mm
Step/Rung distance 280 mm	Step design Rungs	Ladder length as straight ladder (min.) 1.95 m	Ladder length as straight ladder 3.1 m	Ladder length as double-sided ladder (min.) 980 mm
Ladder length as double-sided ladder 1.5 m	Outer width 500 mm	Width of side-rails 25 mm	Max. load capacity 150 kg	Design type Flexible   4-part   Suitable for stairs
Weight 11.88 kg	Transport dimensions 1030 x 495 x 195 mm, 11.88 kg	Business division MUNK Günzburger Steigtechnik	Order no. 032013	Price € 523.00

### Facts

- Aluminium telescopic rung ladder
- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm
- High-strength rung-to-side-rail connection
- Can be used as a step and straight ladder

- Folding in the middle by automatically locking steel hinges
- Both outer sections are telescopic from rung to rung
- Conical side-rail guide for safe stance
- Rung distance: 280 mm
- Maximum load: 150 kg
- Note: Straight ladders over 3.0 m can be used without a stabiliser only when they are used exclusively for their intended purpose (e.g. permanently installed, fitted with hooks, fastened with a belt)
- Note: In accordance with TRBS 2121 Part 2, a suitable accessory is required for working on this ladder

### Scope of supply

- Ladder: 1 x
- Instructions for use and operation: 1 x

### Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany

- **Recyclability:** Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- **Socially acceptable working conditions in production:** fair wages, gender equality
- **Economical and recyclable packaging:** no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- **No health hazards for the users**

More product pictures

---

## Added value

---

### Easy handling

- Centrally mounted, automatically locking steel hinges for quick change of functions
- With Telesteps: Sturdy joints on folding units guarantee durability



### Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



### Flexible use

- Various application options
- Can be used as a height-adjustable step and straight ladder



### Ratchet handles

- Easy to handle thanks to ergonomic shape
- Stable and safe thanks to steel core and aluminium cover



### practical and compact

- Thanks to the telescopic function, the ladders can be folded/moved together to take up minimum space when not in use
- Space-saving storage and easy transport

### Height adjustment

- The height-adjustable ladder sections are ideal for use on stairs
- Intuitive telescoping of the ladder through clearly visible levers or ratchet handles



### Safe standing

- Stabilisers in optimum widths for the ladder model
- Conical construction (without stabiliser) or bevelled rubber shoes



## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

