



Order no.: 062235

Back protection hoop strut, 3,000mm long

Material

Aluminium

Anodised aluminium

Stainless steel

Galvanised steel / hot dip galvanised steel

Specification

Length 3 m	Material Aluminium	Weight 1 kg	Transport dimensions 3000 x 28 x 20 mm, 1 kg	Business division MUNK Günzburger Steigtechnik
Order no. 062235	Price € 51.00	Spare part for article no. 510105	Spare part for article no. 510110	Spare part for article no. 510115
Spare part for article no. 510125	Spare part for article no. 510100	Spare part for article no. 510120		

Facts

- Increases safety when ascending and descending vertical ladders
- For use in demanding environments
- Back protection hoop strut, 3,000 mm long
- C-connector rear protection struts can be ordered separately



Scope of supply

■ Brace: 1 x

Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Optimum planning

- Practical planning aids (available as <u>Downloads</u>) with tips for correct planning of vertical ladder systems
- Planning in close coordination with the client as well as the place and purpose of use
- Joint project planning



All fixed ladders / vertical ladders at a glance:

- Single-flight vertical ladders in accordance with DIN 18799-1/-3, DIN 14094-1 and DIN EN ISO 14122-4 (depending on the choice of standard and the situation on site at the exit, additional components such as exit steps, railings and safety doors may be required)
- DIN 18799-1: Stationary multiple-flight vertical ladders on buildings
- DIN 14094-1: Multiple-flight <u>emergency ladder</u> <u>systems (emergency ladders)</u>
- DIN EN ISO 14122-4: Stationary multiple-flight vertical ladders on machinery



Corporate certifications

on sustainability criteria









