



Order no.: 071302

## Rigid loading bridge LB 300

Type

LB 300

LB 400

LB 500

### Specification

Length <b>2.6 m</b>	Total length max. <b>2.92 m</b>	Extendable <b>No</b>	Foldable <b>No</b>	Total width <b>1.05 m</b>
Clear width <b>1 m</b>	Bridgeable distance <b>2.4 m</b>	Material <b>Aluminium</b>	Permissible total load <b>1000 kg</b>	Surface <b>Aluminium corrugated</b>
Toe board height <b>63 mm</b>	Mobile <b>No</b>	Wheelchair accessible <b>Yes</b>	Weight <b>59 kg</b>	Business division <b>MUNK Rettungstechnik</b>
Order no. <b>071302</b>				

### Facts

- Loading bridge made of non-slip grooved aluminium
- For safe loading and unloading of vehicles and trailers
- With side toe boards

- For professional use

## Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548



**Nachhaltigkeit**  
**EcoVadis**  
sustainable supply management  
CSR-Rating in Silber 2022

