



Order no.: 301303

# Tank truck ladder with rungs type 1



Design

Type 1

Type 2

Type 8

## **Specification**

Version <b>Type 1</b>	Total height max. <b>5.4 m</b>	Total length max. 3.16 m	Total width max. <b>2 m</b>	Platform height max. <b>4.3 m</b>
Platform height min. <b>2.97 m</b>	Platform length 1.08 m	Platform width <b>850 mm</b>	Depth of side-rails <b>93 mm</b>	Depth of side-rails, support <b>25 mm</b>
Max. load capacity <b>150 kg</b>	Swivel castors with locking device Ø 150 mm	Castors, Ø 280 mm <b>0</b>	Weight <b>390 kg</b>	Transport dimensions 3159 x 2000 x 4300 mm, 391 kg
Business division MUNK Günzburger Steigtechnik	Order no. <b>301303</b>	Price <b>€ 16,444.00</b>		

#### **Facts**

- 2-section tanker ladder made of aluminium with platform and protective cage (mandatory element, must be ordered separately)
- Protective cage in three variants can be ordered separately as mandatory equipment
- Stable rectangular tube side-rails



- Rectangular rungs grooved on both sides, 30 x 30 mm
- Optional implementation with steps possible
- 4-fold edged rung-to-side-rail connection
- Guide and connecting parts in stainless steel
- Simple height adjustment from rung to rung thanks to cable winch and locking mechanism
- Platform with grating cover R13
- Railings with toe and knee boards on both sides
- Platform front side with 2-section safety door and protective basket (freely selectable, must be ordered separately)
- Undercarriages partly powder-coated in RAL 1021 and available in three designs
- Rung distance: 280 mm
- Delivery time: 15 days
- Note: The tanker ladder is constructed solely for access when performing operation or inspection tasks during loading or unloading of the tanker

#### Scope of supply

Ladder: 1 x

Chassis: 1 x

## Information on sustainability criteria

Corporate certification: ISO 9001

Corporate certification: ISO 14001

Corporate certification: EN 1090

Corporate certification: EcoVadis

- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct



- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

### More product pictures







#### Added value

#### **Industrial grade**

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



#### Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders





## **Corporate certifications**

on sustainability criteria









