



Order no.: 010112

## Rung straight ladder with standard stabiliser



Number of rungs

12

14

16

18

20

24

### Specification

Working height <b>4.7 m</b>	Step design <b>Rungs</b>	Number of steps/rungs <b>12 rungs</b>	Step/Rung height <b>30 mm</b>	Step depth <b>30 mm</b>
Step/Rung distance <b>280 mm</b>	Type of non-slip protection <b>Aluminium corrugated</b>	Ladder length <b>3.57 m</b>	Outer width <b>420 mm</b>	Stabiliser width <b>930 mm</b>
Depth of side-rails <b>58 mm</b>	Width of side-rails <b>25 mm</b>	Max. load capacity <b>150 kg</b>	Design type <b>To lean against</b>	Weight <b>6.5 kg</b>
Transport dimensions <b>3540 x 425 x 75 mm, 6.5 kg</b>	Business division <b>MUNK Günzburger Steigtechnik</b>	Order no. <b>010112</b>	Price <b>€ 226.00</b>	

### Facts

- Aluminium rung straight ladder
- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection
- Rung distance: 280 mm

- Ladder width: 420 mm (without stabiliser)
- Maximum load: 150 kg
- Standard stabiliser with non-slip ladder shoes with optimum width for the selected product. Ensures maximum stability and safe ascent for straight ladders over 3.0 m. The stabiliser is enclosed separately and is screwed to the lower end of the rail in two places

### Scope of supply

- Ladder: 1 x
- Stabiliser (enclosed separately): 1 x

### Information on sustainability criteria

---

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

## More product pictures

---



## Added value

---

### Standard stabiliser

Safe, standards-compliant ascent for straight ladders over 3.0 m

- Different stabiliser widths, suitable for the selected ladder length
- Non-slip ladder shoes
- Individually available as spare part




### roll-bar retrofit kit

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down



### Note: Working heights

- National regulations (e.g. TRBS 2121 Part 2 in Germany) must be complied with with regard to the maximum working height when using the ladder as a workstation.
- Information on [TRBS 2121 Part 2](#) has been summarised on our Service page
- Read our [tips and tricks](#) on how to calculate [working height](#)



## Certificates

---



17KFP0519-03 -  
Test Certificate  
"Bauart geprüft"

Valid in



DIN EN 131-  
3:2007  
EK5/AK1 17-1:2017  
DIN EN 131-1:2016  
DIN EN 131-2:2017  
PAK-  
ANFORDERUNG  
FÜR GS -  
ABSCHNITT  
3.1(PAH-  
REQUIREMENT  
FOR GS - CL. 3.1)  
AFPS GS 2014:01  
PAK

## Corporate certifications

---

on sustainability criteria



Management System  
ISO 9001:2015  
ISO 14001:2015  
[www.tuv.com](http://www.tuv.com)  
ID 9108612548

