



Order no.: 021714

2-section rung ropeextension ladder with standard stabiliser

Number of rungs

2x14 2x16 2x18 2x20

Specification

Working height	Step design	Number of steps/rungs	Step/Rung height	Step depth
8.3 m	Rungs	2x 14 rungs	30 mm	30 mm
Step/Rung distance	Retracted length	Extended length	Outer width	Stabiliser width
280 mm	4.18 m	7.22 m	420 mm	1.2 m
Depth of side-rails 73 mm	Width of side-rails 25 mm	Design type To lean against 2- part	Weight 22.2 kg	Transport dimensions 4125 x 445 x 169 mm, 22.2 kg
Business division MUNK Günzburger Steigtechnik	Order no. 021714	Price € 800.00		

Facts

- Rung rope-extension ladder made of aluminium
- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm
- 4-fold edged rung-to-side-rail connection



- Convenient height adjustment from rung to rung thanks to two pulleys with plastic cable
- Upper ladder with wall wheels
- Corrosion-resistant guide fixtures with sliding guides
- Rung distance: 280 mm
- Ladder width: 420 mm (without stabiliser)
- Maximum load: 150 kg
- Standard stabiliser with non-slip ladder shoes with optimum width for the selected product. Ensures maximum stability and safe ascent for straight ladders over 3.0 m. The stabiliser is enclosed separately and is screwed to the lower end of the rail in two places
- Note: In accordance with standards, the attached push-up extension ladder section cannot be separated from the ladder with lengths over 3.0 m

Scope of supply

- Ladder: 1 x
- Stabiliser (enclosed separately): 1 x

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: ISO 14001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems

Instructions for use and operation: 1 x



- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.
- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



Optimum and smooth operation, thanks to easily accessible elements

- Simple height adjustment from rung to rung or from step to step
- Wall wheels on the upper part (from 14 rungs or more)
- Fittings with sliding guides
- Smooth-running rope pulley



Standard stabiliser

Safe, standards-compliant ascent for straight ladders over 3.0 m

- Different stabiliser widths, suitable for the selected ladder length
- Non-slip ladder shoes
- Individually available as spare part





roll-bar retrofit kit

- Rolling instead of carrying: ergonomic and convenient handling
- Simple, no-drill mounting on stabilisers
- User-friendly operation without bending down



Certificates

17KFP1539-03 - Test Certificate "Bauart geprüft" Valid in
DIN EN 131-3:2007 PAK- ANFORDERUNG FÜR GS - ABSCHNITT 3.1(PAH- REQUIREMENT FOR GS - CL. 3.1) AFPS GS 2014:01 PAK EK5/AK1 17-1:2017 DIN EN 131-1:2016 DIN EN 131-2:2017



Corporate certifications

on sustainability criteria



