MUNK
Sicherheit. Made in Germany.



Order no.: 115476

Telescopic combination ladder Combi Line

Number of steps

5 + 2

Specification

Working height max. 3.1 m	Number of steps/rungs 1x5 St. 1x2 St.	Step depth 90 mm	Step design Steps	Retracted length 690 mm
Extended length 2.34 m	Outer width 690 mm	Stabiliser width 690 mm	Max. load capacity 150 kg	Design type Freestanding | Double-sided access
Transport dimensions (plus packaging) 740 x 480 x 200 mm, 15.5 kg	Business division MUNK Günzburger Steigtechnik	Order no. 115476		

Facts

- Original Telesteps telescopic ladder made of aluminium
- Sturdy triangular side-rails, anodised for abrasion resistance
- 90 mm deep steps with line profiles to minimise the risk of slipping
- High-strength step-to-side-rail connection
- Convenient height adjustment through intuitive telescopic function

- Can be used as a step and straight ladder
- Easy to transport thanks to integrated carrying handle (enclosed loose)
- Folds together compactly
- Maximum load: 150 kg
- Tool tray optionally available as an accessory
- These products are covered by the statutory warranty

Scope of supply

- Ladder: 1 x
- Carry handle (enclosed separately): 1 x
- Instructions for use and operation: 1 x

More product pictures







Added value

Easy handling

- Centrally mounted, automatically locking steel hinges for quick change of functions
- With Telesteps: Sturdy joints on folding units guarantee durability



Ratchet handles

- Easy to handle thanks to ergonomic shape
- Stable and safe thanks to steel core and aluminium cover



Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



practical and compact

- Thanks to the telescopic function, the ladders can be folded/moved together to take up minimum space when not in use
- Space-saving storage and easy transport

Flexible use

- Various application options
- Can be used as a height-adjustable step and straight ladder



Height adjustment

- The height-adjustable ladder sections are ideal for use on stairs
- Intuitive telescoping of the ladder through clearly visible levers or ratchet handles



Safe standing

- Stabilisers in optimum widths for the ladder model
- Conical construction (without stabiliser) or bevelled rubber shoes



Certificates



Z1 070102 0011
Rev. 0 - Certificate

Valid in

DIN EN 131-6:2019
DIN EN 131-1:2015/A1:2019
DIN EN 131-3:2018

Corporate certifications

Standards for quality and sustainability

